

January 7, 1998

TEL:805-498-2111 FAX:805-498-3804 WEB:http://www.semtech.com

AXIAL LEADED HERMETICALLY SEALED SUPERFAST RECTIFIER DIODE

QUICK REFERENCE DATA


- Very low reverse recovery time
- Hermetically sealed with Metoxilite fused metal oxide
- Low thermal impedance
- Low switching losses
- Soft, non-snap off, recovery characteristics

- $V_R = 200 - 400V$
- $I_F = 2.1A$
- $t_{rr} = 50ns$
- $I_R = 10\mu A$

ABSOLUTE MAXIMUM RATINGS (@ 25°C unless otherwise specified)

	Symbol	USC1104	USC1105	USC1106	Unit
Working reverse voltage	VRWM	200	300	400	V
Repetitive reverse voltage	VRRM	200	300	400	V
Average forward current (@ 55°C, lead length = 0.375")	IF(AV)	←	2.1	→	A
Repetitive surge current (@ 55°C in free air, lead length 0.375")	IFRM	←	9.0	→	A
Non-repetitive surge current (tp = 8.3mS, @ VR & Tjmax)	IFSM	←	20	→	A
Storage temperature range	TSTG	←	-55 to +150	→	°C
Operating temperature range	TOP	←	-55 to +150	→	°C

MECHANICAL



January 7, 1998

ELECTRICAL CHARACTERISTICS (@ 25°C unless otherwise specified)

	Symbol	USC1104	USC1105	USC1106	Unit
Average forward current max. (pcb mounted; $T_A = 55^\circ\text{C}$) for sine wave	$I_{F(AV)}$	←	1.0	→	A
for square wave ($d = 0.5$)	$I_{F(AV)}$	←	1.1	→	A
Average forward current max. ($T_L = 55^\circ\text{C}$; $L = 3/8"$) for sine wave	$I_{F(AV)}$	←	2.0	→	A
for square wave	$I_{F(AV)}$	←	2.1	→	A
I^2t for fusing ($t = 8.3\text{mS}$) max.	I^2t	←	1.7	→	A ² S
Forward voltage drop max. @ $I_F = 1.0\text{A}$, $T_j = 25^\circ\text{C}$	V_F	←	1.25	→	V
Reverse current max. @ V_{RWM} , $T_j = 25^\circ\text{C}$	I_R	←	10	→	μA
@ V_{RWM} , $T_j = 100^\circ\text{C}$	I_R	←	200	→	μA
Reverse recovery time max. 0.5A I_F to 1.0A I_R . Recovers to 0.25A I_{RR} .	t_{rr}	←	50	→	nS
Junction capacitance typ. @ $V_R = 5\text{V}$, $f = 1\text{MHz}$	C_j	←	25	→	pF

THERMAL CHARACTERISTICS

	Symbol	USC1104	USC1105	USC1106	Unit
Thermal resistance - junction to lead Lead length = 0.0"	$R_{\theta JL}$	←	7	→	°C/W
Lead length = 0.375"	$R_{\theta JL}$	←	38	→	°C/W
Thermal resistance - junction to amb. on 0.06" thick pcb. 1 oz. copper.	$R_{\theta JA}$	←	95	→	°C/W