



### 1. CONFIGURATION & DIMENSIONS :



UNIT : mm (inch)

SIZE	L	W	H	A	B	gram
12	64.70 (2.547)	50.00 (1.969)	26.30 (1.035)	50.80 (2.000)	12.70 (0.500)	311.85

### 2. SCHEMATIC :



### 3. ELECTRICAL CHARACTERISTICS (@ 25°C) :

- |                                      |                              |
|--------------------------------------|------------------------------|
| a. Primary Voltage                   | AC 115/230 V 50/60 Hz .      |
| b. NO Load Primary Current           | Less Than 30mA .             |
| Input AC 115V 60Hz .                 | Less Than 30mA .             |
| Input AC 230V 50Hz .                 | Series AC 15.30V .           |
| c. Secondary Voltage (±5%)           | Parallel AC 7.65V .          |
| d. Secondary Load Current            | Series 900mA .               |
| e. Full Load Primary Current         | Parallel 1800mA .            |
| Input AC 115V 60Hz .                 | Less Than 80mA .             |
| Input AC 230V 50Hz .                 | Less Than 150mA .            |
| f. Full Load Secondary Voltage (±5%) | Series 12.60V .              |
| g. DC Resistance                     | Parallel 6.30V .             |
| Pin 1-2                              | Primary = 146 Ohm .          |
| Pin 3-4                              | = 146 Ohm .                  |
| Pin 5-6                              | Secondary = 0.69 Ohm .       |
| Pin 7-8                              | = 0.69 Ohm .                 |
| h. Insulation Resistance             | DC 500V 100Meg Ohm Of More . |
| i. Withstand Voltage (Hi-Pot)        | AC 1500V 60Hz 1 Minutes .    |
| j. Temperature Rise                  | Less Than 60 Deg C .         |
| k. Core Size                         | UI-38 x 13.00 m/m .          |



**RoHS Compliant**

NOTE : Specifications subject to change without notice. Please check our website for latest information.

05.06.2008



**SUPERWORLD ELECTRONICS (S) PTE LTD**