



MARK: KINGS 791-9-9 (DATE CODE)

- NOTES: FOR USE WITH BOEING BMS13-65 OF & ADAMS RUSSELL FC14Z CABLE.
- FOR CABLING INSTRUCTIONS SEE 3-546-2.
 - FOR CRIMPING USE DIE KTH-2211.
 - FOR USE WITH .188 MAX. PANEL.
 - CENTER CONTACT (1-842-23MA9) SUPPLIED UNASSEMBLED.
 - INTERFACE PER MIL-STD-348, FIG. 302-2.
 - MARK PACKAGE: KINGS 791-9-9 (DATE CODE)
 - MATERIALS:
INSULATOR-TEFLON, ASTM D1710
K-GRIP SLEEVE-COMMERCIAL BRONZE, ASTM B135
CENTER CONTACT-BER. COP., ASTM B196
ALL OTHER METAL PARTS-BRASS, ASTM B16
 - FINISHES:
CENTER CONTACT: .000050 MIN GOLD PLATE, PER ASTM B488 OVER
.000050 MIN. NICKEL PER AMS-QQ-N-290 (RoHS)
ALL OTHER METAL PARTS: .000050 MIN NICKEL PER AMS-QQ-N-290
OVER .000050 MIN COPPER PER ASTM B734 (RoHS)

- ELECTRICAL CHARACTERISTICS:
NOMINAL IMPEDANCE-50 OHMS
FREQUENCY RANGE-DC TO 11 GHZ
WORKING VOLTAGE-1000 VRMS
- PROTECTIVE CAP TO BE SUPPLIED ASSEMBLED.
- WEIGHT: 26.7 GRAMS

#4-40 UNC-2B TH'D
LOCKING THREAD
(4 PLACES)

791-9-9

REVISIONS	
ISSUE	CHANGES
0	ER 36838 VLS 02/15/96
1	CN 36939 A KH 04/23/96
2	CN 37437 A VLS 09/08/98
D	REVISED PER DMF304& ER35452 KPL 10/18/11

CUSTOMER
SALES
DRAWING

THIS DRAWING, THE DESIGNS AND IDEAS EMBODIED IN THE DEVICE TO WHICH IT RELATES, AND THE METHOD OF PRODUCING THE DEVICE, ARE THE PROPERTY OF WINCHESTER ELECTRONICS CORPORATION AND SHALL NOT BE EMPLOYED, COPIED, OR DISCLOSED TO ANYONE, IN ANY MANNER WITHOUT THE CONSENT OF WINCHESTER ELECTRONICS CORPORATION.

SCALE 4:1

APPROX SURFACE AREA

CAGE CODE: 91836

REF: BOEING

JACK, PANEL, C

DRAWN	VLS	DATE	02/15/96
DESIGN	VLS	DATE	02/15/96
APPR.	VLS	DATE	02/15/96

WINCHESTER ELECTRONICS CORPORATION
62 Barnes Industrial Road North
Wallingford, Connecticut 06492

791-9-9