



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

Approval Sheet For Product Specification

Issued Date:

Product Name: SAW Resonator 622.31 MHz SMD 3X3 mm

TST Parts No.: TC0246A

Customer Parts No.: _____

Company: _____

Division: _____

Approved by : _____

Date: _____

Checked by: _____ Vincent-WT Chiu

Approval by: _____ Francis Chen

Date: _____ 2004/05/14



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

SAW Resonator 622.31 MHz

MODEL NO.: TC0246A

REV. NO.:1

A. FEATURES:

1. 1-Port Resonator.

B. MAXIMUM RATING:

1. Input Power Level: 0 dBm
2. DC voltage: 12 V
3. Operating Temperature: -40°C to +85°C
4. Storage Temperature: -40°C to +85°C

RoHS Compliant
Lead free
Lead-free soldering


C. ELECTRICAL CHARACTERISTICS:

Reference Temperature $T_A=25^{\circ}\text{C}$

Characteristic	Units	Minimum	Typical	Maximum
Center frequency F_c	MHz	622.27	622.31	622.34
Insertion Loss IL	dB	-	1.3	2.0
Unload quality factor Q_U		10000	11300	-
Ageing of f _c	ppm/yr	-	-	±10
Motional capacitance C₁	fF	-	1.64	-
Motional inductance L₁	μH	-	39.89	-
Motional resistance R₁	Ohm	-	13.75	-
Parallel capacitance C₀	pF	-	2.92	-
Frequency Temperature coefficient (C _f)	ppm/c*2	-	0.032	-
Turnover To	deg.C	10		40
Package size		SMD 3x3x1.1 mm		


Temperature dependence of f_c: $f_c(T_A)=f_c(T_O)(1+TC_f(T_A-T_O)^2)$

D. OUTLINE DRAWING:



E. EQUIVALENT CIRCUIT:


One-Port Resonator:




F. FREQUENCY CHARACTERISTICS:



G. TEST CIRCUIT:




H. LAND PATTERN:



I. PACKING:

1. REEL DIMENSION



2. TAPE DIMENSION

