



P.C.B LAYOUT

MATERIAL & FINISHES
 INSULATOR - PBT GLASS FILLED U194V-0
 CONTACT- BRASS
 SHELL - STEEL
 PLATING - GOLD FLASH
 ELECTRICAL CHARACTERISTICS
 RATING CURRENT : 3A
 CONTACT RESISTANCE : <20mΩ
 INSULATION RESISTANCE : >1000MΩ at 500V
 DIELECTRIC VOLTAGE : 1000V /MIN
 OPERATING TEMPERATURE : -50 ° C TO+105 ° C

POLFS	PART No.	Dim. A	Dim. B	Dim. C	Dim. D
9	DMS-9P	16.92	24.99	30.81	19.25
15	DMS-15P	25.25	33.32	39.14	27.51
25	DMS-25P	38.96	47.04	53.04	41.20
37	DMS-37P	55.42	63.50	69.40	57.5

TOLERANCE TABLE

.0	±0.20
.00	±0.10
.000	±0.05

APPROVED:	DATE:	深圳市灿科盟实业有限公司 CHANKLEMENT INDUSTRYCO., LTD
CHECKED:	DATE:	
DRAWN:	DATE:	TITLE:
LYF	2010-11-02	DMS-XP 公头 光孔
P/N / UNIT mm SCALE free FILE NO. Ckmtw-DMS-0001 REV. A HX00		