

**RoHS SIDACtor® Series - DO-15**



**Agency Approvals**

| Agency | Agency File Number |
|--------|--------------------|
|        | E133083            |

**Pinout Designation**

Not Applicable

**Schematic Symbol**



**Description**

The SIDACtor Series DO-15 are designed to protect baseband equipment such as modems, line cards, CPE and DSL from damaging overvoltage transients.

The series provides a cost-effective through-hole solution that enables equipment to comply with global regulatory standards.

**Features and Benefits**

- Low voltage overshoot
- Low on-state voltage
- Does not degrade with use
- Fails short circuit when surged in excess of ratings
- Low Capacitance

**Applicable Global Standards**

- TIA-968-A
- TIA-968-B
- ITU K.20/21 Enhanced Level\*
- ITU K.20/21 Basic Level
- GR 1089 Inter-building\*
- GR 1089 Intra-building
- IEC 61000-4-5
- YD/T 1082
- YD/T 993
- YD/T 950

\* A/B-rated parts require series resistance

**Electrical Characteristics**

| Part Number | Marking | $V_{DRM}$<br>@ $I_{DRM}=5\mu A$ | $V_s$<br>@ 100V/ $\mu s$ | $I_H$  | $I_s$  | $I_T$ | $V_T$<br>@ $I_T=2.2$ Amps | Capacitance<br>@ 1MHz, 2V bias |        |
|-------------|---------|---------------------------------|--------------------------|--------|--------|-------|---------------------------|--------------------------------|--------|
|             |         | V min                           | V max                    | mA min | mA max | A max | V max                     | pF min                         | pF max |
| P1100GALRP  | P11A    | 90                              | 130                      | 150    | 800    | 2.2   | 5                         | 30                             | 60     |
| P1300GALRP  | P13A    | 120                             | 160                      | 150    | 800    | 2.2   | 5                         | 25                             | 40     |
| P1500GALRP  | P15A    | 140                             | 180                      | 150    | 800    | 2.2   | 5                         | 25                             | 40     |
| P1800GALRP  | P18A    | 170                             | 220                      | 150    | 800    | 2.2   | 5                         | 25                             | 40     |
| P2300GALRP  | P23A    | 190                             | 260                      | 150    | 800    | 2.2   | 5                         | 25                             | 30     |
| P2600GALRP  | P26A    | 220                             | 300                      | 150    | 800    | 2.2   | 5                         | 25                             | 30     |
| P3100GALRP  | P31A    | 275                             | 350                      | 150    | 800    | 2.2   | 5                         | 20                             | 30     |
| P3500GALRP  | P35A    | 320                             | 400                      | 150    | 800    | 2.2   | 5                         | 20                             | 30     |
| P1100GBLRP  | P11B    | 90                              | 130                      | 150    | 800    | 2.2   | 5                         | 30                             | 60     |
| P1300GBLRP  | P13B    | 120                             | 160                      | 150    | 800    | 2.2   | 5                         | 25                             | 40     |
| P1500GBLRP  | P15B    | 140                             | 180                      | 150    | 800    | 2.2   | 5                         | 25                             | 40     |
| P1800GBLRP  | P18B    | 170                             | 220                      | 150    | 800    | 2.2   | 5                         | 25                             | 40     |
| P2300GBLRP  | P23B    | 190                             | 260                      | 150    | 800    | 2.2   | 5                         | 25                             | 30     |
| P2600GBLRP  | P26B    | 220                             | 300                      | 150    | 800    | 2.2   | 5                         | 25                             | 30     |
| P3100GBLRP  | P31B    | 275                             | 350                      | 150    | 800    | 2.2   | 5                         | 20                             | 30     |
| P3500GBLRP  | P35B    | 320                             | 400                      | 150    | 800    | 2.2   | 5                         | 20                             | 30     |

Notes:

- Absolute maximum ratings measured at  $T_A = 25^\circ C$  (unless otherwise noted).
- Devices are bi-directional.

## Surge Ratings

| Series | $I_{PP}$                                   |                                              | $I_{TSM}$  |
|--------|--------------------------------------------|----------------------------------------------|------------|
|        | 10x560 <sup>1</sup><br>10x560 <sup>2</sup> | 10x1000 <sup>1</sup><br>10x1000 <sup>2</sup> | 50 / 60 Hz |
|        | Amps min                                   | Amps min                                     | Amps min   |
| A      | 50                                         | 45                                           | 20         |
| B      | 100                                        | 80                                           | 25         |

Notes:

1 Current waveform in  $\mu s$


2 Voltage waveform in  $\mu s$

- Peak pulse current rating ( $I_{PP}$ ) is repetitive and guaranteed for the life of the product.

-  $I_{PP}$  ratings applicable over temperature range of -40 to +85°C


- The device must initially be in thermal equilibrium with -40°C  $\leq T_J \leq$  +150°C

## Thermal Considerations

| Package                                                                                    | Symbol          | Parameter                               | Value       | Unit |
|--------------------------------------------------------------------------------------------|-----------------|-----------------------------------------|-------------|------|
| <br>DO-15 | $T_J$           | Operating Junction Temperature Range    | -40 to +150 | °C   |
|                                                                                            | $T_S$           | Storage Temperature Range               | -65 to +150 | °C   |
|                                                                                            | $R_{\theta JA}$ | Thermal Resistance: Junction to Ambient | 60          | °C/W |

## Soldering Parameters


| Reflow Condition                                       |                                   | Pb-Free assembly<br>(see Fig. 1) |
|--------------------------------------------------------|-----------------------------------|----------------------------------|
| Pre Heat                                               | -Temperature Min ( $T_{s(min)}$ ) | +150°C                           |
|                                                        | -Temperature Max ( $T_{s(max)}$ ) | +200°C                           |
|                                                        | -Time (Min to Max) ( $t_s$ )      | 60-180 secs.                     |
| Average ramp up rate (Liquidus Temp ( $T_L$ ) to peak) |                                   | 3°C/sec. Max.                    |
| $T_{s(max)}$ to $T_L$ - Ramp-up Rate                   |                                   | 3°C/sec. Max.                    |
| Reflow                                                 | -Temperature ( $T_L$ ) (Liquidus) | +217°C                           |
|                                                        | -Temperature ( $t_L$ )            | 60-150 secs.                     |
| Peak Temp ( $T_p$ )                                    |                                   | +260(+0/-5)°C                    |
| Time within 5°C of actual Peak Temp ( $t_p$ )          |                                   | 30 secs. Max.                    |
| Ramp-down Rate                                         |                                   | 6°C/sec. Max.                    |
| Time 25°C to Peak Temp ( $T_p$ )                       |                                   | 8 min. Max.                      |
| Do not exceed                                          |                                   | +260°C                           |




## Physical Specifications

|                        |                                                               |
|------------------------|---------------------------------------------------------------|
| <b>Lead Material</b>   | Copper Alloy                                                  |
| <b>Terminal Finish</b> | 100% Matte-Tin Plated                                         |
| <b>Body Material</b>   | UL recognized epoxy meeting flammability classification 94V-0 |

## Part Marking



## Part Numbering




## Environmental Specifications

|                                         |                                                                                                                       |
|-----------------------------------------|-----------------------------------------------------------------------------------------------------------------------|
| <b>High Temp Voltage Blocking</b>       | 80% Rated $V_{DRM}$ ( $V_{AC}$ Peak) +125°C or +150°C, 504 or 1008 hrs. MIL-STD-750 (Method 1040) JEDEC, JESD22-A-101 |
| <b>Temp Cycling</b>                     | -65°C to +150°C, 15 min. dwell, 10 up to 100 cycles. MIL-STD-750 (Method 1051) EIA/JEDEC, JESD22-A-104                |
| <b>Biased Temp &amp; Humidity</b>       | 52 $V_{DC}$ (+85°C) 85% RH, 504 up to 1008 hrs. EIA/JEDEC, JESD22-A-101                                               |
| <b>High Temp Storage</b>                | +150°C 1008 hrs. MIL-STD-750 (Method 1031) JEDEC, JESD22-A-101                                                        |
| <b>Low Temp Storage</b>                 | -65°C, 1008 hrs.                                                                                                      |
| <b>Thermal Shock</b>                    | 0°C to +100°C, 5 min. dwell, 10 sec. transfer, 10 cycles. MIL-STD-750 (Method 1056) JEDEC, JESD22-A-106               |
| <b>Autoclave (Pressure Cooker Test)</b> | +121°C, 100% RH, 2atm, 24 up to 168 hrs. EIA/JEDEC, JESD22-A-102                                                      |
| <b>Resistance to Solder Heat</b>        | +260°C, 30 secs. MIL-STD-750 (Method 2031)                                                                            |
| <b>Moisture Sensitivity Level</b>       | 85% RH, +85°C, 168 hrs., 3 reflow cycles (+260°C Peak). JEDEC-J-STD-020, Level 1                                      |

## Packing Options


| Package Type | Description             | Quantity | Added Suffix | Industry Standard |
|--------------|-------------------------|----------|--------------|-------------------|
| G            | DO-15 Axial Tape & Reel | 5000     | RP           | EIA-RS-296-D      |

## Dimensions — DO-15



| Dimension | Inches |       | Millimeters |       |
|-----------|--------|-------|-------------|-------|
|           | MIN    | MAX   | MIN         | MAX   |
| <b>B</b>  | 0.028  | 0.034 | 0.711       | 0.864 |
| <b>D</b>  | 0.12   | 0.14  | 3.048       | 3.556 |
| <b>G</b>  | 0.235  | 0.27  | 5.969       | 6.858 |
| <b>L</b>  | 1      |       | 25.4        |       |

## Tape and Reel Specification — DO-15



| Symbols  | Description                      | Inches         | MM            |
|----------|----------------------------------|----------------|---------------|
| <b>A</b> | Component Spacing (lead to lead) | 0.200 ± 0.020" | 5.08 ± 0.508  |
| <b>B</b> | Inner Tape Pitch                 | 2.062 ± 0.059" | 52.37 ± 1.498 |
| <b>C</b> | Tape Width                       | 0.250"         | 6.35          |
| <b>D</b> | Max. Off Alignment               | 0.048"         | 1.219         |
| <b>E</b> | Reel Dimension                   | 13"            | 330.2         |
| <b>F</b> | Max. Hub Recess                  | 3"             | 76.19         |
| <b>G</b> | Max. Abor Hole                   | 0.68"          | 17.27         |