



258FSB330XFQ

PHOTOFLASH ALUMINUM ELECTROLYTIC CAPACITORS

Parts are RoHS compliant

Date code when parts became RoHS: 1327

APPLICATIONS: Photoflash, strobes, Security systems

ELECTRICAL SPECIFICATIONS

Capacitance: 2500 μ F

Dissipation Factor: 0.15 Max at 120 Hz and 20°C

Temperature Range: -20°C to +55°C

Impedance: N/A

Tolerance: -20 %, +50 %

WVDC: 330 Volts DC

SVDC: 350 Volts DC

Ripple Current: at and

Impedance Ratios:- and - -

Leakage Current: 1°C

2500 μ A after 5 Minutes

Charge/discharge: 5000 charge/discharge cycles at rated voltage & 5~35°C repeating every 30 seconds thru a Xe tube having a discharge resistance of 0.7 to 1 Ohm

Capacitance Change: $\leq 10\%$ of initial measured value

Dissipation Factor: $\leq 150\%$ of maximum specified value

Leakage Current: $\leq 150\%$ of maximum specified value

Frequency Multipliers:

50 HZ	120 HZ	400 HZ	1 KHZ	10 KHZ	100 KHZ
1	1	1	1	1	1

Temperature Multipliers:

45°C	60°C	70°C	65°C	75°C	85°C	105°C	125°C
1	1	1	1	1	1	1	0

PHYSICAL DIMENSIONS

Diameter (D): 40 mm + 1 mm

Length (L): 75 mm + 2 mm


Lead Spacing (S): 14 mm +/- 1 mm

Coating: BlackPVC sleeving

Lead Wire Diameter (d): 5 mm +/- 0.2 mm

Lead Length: 10 mm +/- 1.5 mm

Lead Finish: Matte Tin



3757 W. Touhy Ave. Lincolnwood, IL 60712 (847) 675-1760 FAX (847) 673-2850
Illinois Capacitor (HK) Ltd., Tel: 85227930931, Fax: 85227930731, www.illcap.com.hk
© Copyright 2019 Illinois Capacitor. An affiliate of Cornell Dubilier, All Rights Reserved