




High Isolation Multi-Purpose Audio Transformers

Ideal for a variety of Voice and Data interconnect network applications

- ☛ 3000 V_{RMS} minimum Isolation
- ☛ Longitudinal Balance is 60dB minimum
- ☛ Frequency range: 300Hz to 3400Hz
- ☛ Designed to meet FCC part 68
- ☛ Materials used in construction of this component meet or exceed UL Class B and can operate up to 130°C



Dry / High Performance

Electrical Specifications at 25°C

Part Number	Impedance (Ohms)	UNBAL. DC (mA)	Insertion Loss ⁽¹⁾ (dB)	Frequency Response (dB)	Return Loss ⁽²⁾ (dB)	Pri. DCR max. (Ω)	Sec. DCR max. (Ω)	Schem. Style
T-30700	600 / 600	0.0	1.5	0.3	20	45	45	A
T-30701	600 / 600CT	0.0	1.5	0.3	20	45	45	B
T-30702	600CT / 600CT	0.0	1.5	0.3	20	45	45	C
T-30703	600 / 900	0.0	1.5	0.5	20	45	55	A
T-30704	900 / 900	0.0	1.5	0.5	20	55	55	A

Dry / Economy

Electrical Specifications at 25°C

Part Number	Impedance (Ohms)	UNBAL. DC (mA)	Insertion Loss ⁽¹⁾ (dB)	Frequency Response (dB)	Return Loss ⁽²⁾ (dB)	Pri. DCR max. (Ω)	Sec. DCR max. (Ω)	Schem. Style
T-30750	600 / 600	0.0	1.7	0.5	20	45	45	A
T-30751	600 / 600CT	0.0	1.7	0.5	20	45	45	B
T-30752	600CT / 600CT	0.0	1.7	0.5	20	45	45	C
T-30753	600 / 900	0.0	1.7	0.7	20	45	55	A
T-30754	900 / 900	0.0	1.7	0.7	20	55	55	A

1. Insertion Loss measured at 1 KHz
2. Return Loss measured at 300 Hz

Dimensions in Inches (mm)

Unused Pins Omitted as Per Schematic

