


Data sheet | Item number: 788-931

Basic relay; Nominal input voltage: 24 VDC; 1 changeover contact; Limiting continuous current: 16 A; with manual operation; Module width: 13 mm


www.wago.com/788-931



Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Data

Technical data

Control circuit

Nominal input voltage U_N DC 24 V

Load circuit

Number of changeover/switchover contacts	1
Contact material (relay)	AgNi
Limiting continuous current	16 A
Inrush current (resistive) (max.)	(AC) 24 A
Switching voltage (max.)	AC 250 V
Switching power (resistive) (max.)	AC 4000 VA; DC (see load limit curve)
Switching capacity	AC-15: 3 A / AC 240 V; DC-13: 2 A / DC 24 V
Recommended minimum load	12 V / 10 mA
Pull-in time (typ.)	15 ms
Drop-out time (typ.)	8 ms
Bounce time (typ.)	6 ms
Electrical life (NO; resistive load; 23 °C)	10×10^3 switching operations
Mechanical life	5×10^6 switching operations
Switching frequency with/without load (max.)	6 min^{-1} / 300 min^{-1}

Subject to changes. Please also observe the further product documentation!



Signaling

Status indicator	Mechanical
------------------	------------

Safety and protection

Dielectric strength, control/load circuit (AC, 1 min)	5 kVrms
---	---------

Dielectric strength, open contact (AC, 1 min)	1 kVrms
---	---------

Protection type	IP20
-----------------	------

Material data

Weight	15.2 g
--------	--------

Commercial data

PU (SPU)	8 Stück
----------	---------

Packaging type	box
----------------	-----

Downloads

Documentation

Additional Information

Disposal; Electrical and electronic equipment, Packaging	V 1.0.0	pdf 265.8 kB	Download
--	---------	-----------------	----------

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 788-931	URL	Download
--	-----	----------

Basic relay; Nominal input voltage: 24 VDC; 1 changeover contact; Limiting continuous current: 16 A; with manual operation; Module width: 13 mm

Installation Notes

Subject to changes. Please also observe the further product documentation!