

PCB LAYOUT
TOP VIEW

SPECIFICATIONS:

规格:

RATING: 12V DC @ 1A

额定值: 12V DC@1A

CONTACT RESISTANCE: 30m OHMS MAX

接触电阻: 最大30m欧姆

INSULATION RESISTANCE: 100M OHMS MIN: 500V DC

绝缘电阻: 100M OHMS MIN: 500V DC

VOLTAGE WITHSTAND: 500V AC R.M.S. FOR 1 MINUTE


耐压: 500V AC R.M.S. FOR 1 MINUTE

LIFE: 5,000 CYCLES

寿命: 5000个周期

OPERATING TEMP: -20° ~ +85°C

工作温度: -20°C ~ +85°C



	MATERIAL	PLATING
center pin	Brass	tin
terminal 1	Brass	tin
terminal 2	Phosphor Bronze	tin
terminal 3	Brass	tin
plastic	Pbt	

广东星坤科技股份有限公司

生

日

效


期

文件工程章

MARK	DESCRIPTION	REVISIONS	DATE	REVISED	APPROVED

ANGULAR	±5°
X.X	±0.2mm
X.XX	±0.1mm
X.XXX	±0.05mm

UNSPECIFIED TOLERANCES

DSND	DATE	SCALE: N/A	MODEL TYPE: DC POWER JACK
DWN	DATE	VIEW: 	PART NO.:
CHKD	DATE	UNIT: mm/in	DWG NO.: DC-023
APPD	DATE	SIZE: A4	REVISION
XKB INDUSTRIAL PRECISION CO., LIMITED			WEIGHT 1.0g
			SHEET 1/1
			REVISION A0