


Fuse terminals

SAKS 3 SAKS 3/35



Dimensions/approvals	
Width/length/height (mm)	with TS 32
Width/length/height (mm)	with TS 35 x 7.5
Insulation stripping length/clamping screw/screwdriver blade	

13/54/61
13/54/55
12 mm/M 4/5.5 x 1

SAKS 4 SAKS 4/35



24/75/73

24/75/66

14 mm/M 4/5.5 x 1

SAKS 5 SAKS 5/35



28/80/80.5

28/80/66

13 mm/M 4/5.5 x 1

SAKS 2 SAKS 2/35



28/80/81.5

28/80/75

12 mm/M 4/5.5 x 1

Rated data/feed through-terminal base	
Rated voltage/current/cross-section	500 V/10 A/10 mm ²
Rated impulse voltage/pollution severity	6 kV/3

Further technical data	
Tightening torque range	Nm 1.2...2.4
Torque setting with electric screwdriver type DMS 2	4

Clampable conductor	
Solid H07V-U	mm ² 0.5...16
Stranded H07V-R	mm ² 1.5...10
Flexible H07V-K	mm ² 0.5...10
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ² 0.5...10
Plug gauge according to 60 947-7-1	Size B 6
Continuous current rating of cross-connection 2...5-pole	A (QL 2...5) 47
Continuous current rating of cross-connection 6...10-pole	A (QL 6...10) 36

Rated data according to UL/CSA	
Voltage/current/conductor size	UL 300 V/10 A/22...10 AWG
Voltage/current/conductor size	CSA 600 V/10 A/22...10 AWG

Ordering data	
Version	

KrG **0248920000**³⁾ **0667520000**³⁾ **0297520000**⁴⁾ **0328920000**⁴⁾

Neozed D 01
Type Cat. No. Qty.
TW HP (2.0) **0607000000*** 20

Neozed D 02
Type Cat. No. Qty.
TW HP (2.0) **0607000000*** 20

Diazed E 16
Type Cat. No. Qty.
TW HP (2.0) **0607000000*** 20

End plate/partition (thickness mm)	
PA	Type Cat. No. Qty. AP (2.5) 0191320000
HP	for TW (2.0) 0607000000

Cross-connection	
QL	SS

Fuse inserts	
---------------------	--

1 1/4" x 1/4"	Nominal current (A): 0.5 fast	E 0.5 A 0533800000
	1.0 fast	E 1 A 0525500000
	2.0 fast	E 2 A 0294500000
	3.0 fast	E 3 A 0295700000
	5.0 fast	E 5 A 0294600000
	7.0 fast	E 7 A 0295800000
	10.0 fast	E 10 A 0293900000

G fuse inserts 5 x 30 mm
(500 V~/0.032...6.3 A).
Available from Wickmann-Werke GmbH,
Annstr. 113, 58453 Witten, Germany, Phone ++492302/6620

D fuse inserts	
Rated voltage 400 V	E 14/2 0137400000 10
	E 14/4 0137500000 10
	E 14/6 0328300000 10
	E 14/10 0328400000 10
	E 14/16 0328500000 10

Screw cap (spare)	
red	SK (5 x 30) 0282000000 20
black	SK (1/4"x1 1/4") 0428900000 20

Marking tags	
	DEK Standard DEK 5 see "Accessories"

Mounting rails, end brackets, further marking material see "Accessories"

¹⁾ only for TS 32

²⁾ Also for 440 V- with neozed marina fuse
³⁾ Current for overload up to 10 A, for short circuit up to 25 A

³⁾ For fuse inserts 1 1/4" x 1/4" DEF 63
⁴⁾ For fuse inserts 5 x 30