



Specifications:

规格:
Voltage rating: 250V AC/DC
 额定电压: 250V AC/DC
Current rating: 3A AC/DC
 额定电流: 3A AC/DC
Withstanding voltage: 800V AC/minute
 耐受电压: 800V AC/分钟
Temperature range: -25°C ~ +85°C
 温度范围: -25°C ~ +85°C
Insulation resistance: ≥1000MΩ
 绝缘电阻: ≥1000MΩ
Contact resistance: ≤10mΩ
 接触电阻: ≤10mΩ
After environmental testing: ≤20mΩ
 环境测试后: ≤20兆欧

X2026 T X- P XXX X - B
 ① ② ③ ④ ⑤ ⑥ ⑦

1. Series Number
2. Category: T-terminal
3. Shape: Blank-Ordinary
4. Material: P-Phosphor bronze
5. Plating style: SN-Bright tin plating
6. Plating method: Blank-Stamping before plating
7. Mold No/Mark/Special No: B-With Lock In the middle

X2026T-PSN-B	Phosphor Bronze	AWG#22-28	1.5mm(Max)	Plating Before Stamping: 10u"Ni; 40~60u"Sn	X2026H-B
PART NO	Material	Wire Range	Insulation OD	Finish	Suitable XKB Terminal

广东星坤科技股份有限公司

生	日期
效	日期
效	日期
效	日期
MARK	文件工程章

SEC: B-B

SEC: A-A

DSND		DATE		SCALE: N/A	MODEL TYPE: Wire to board connector
DWN		DATE		VIEW:	PART NO.: 2.00mm Crimp Style Connectors
CHKD		DATE		UNIT: mm/in	DWG NO.: X2026T-PSN-B
APPD		DATE		SIZE: A4	
KKB INDUSTRIAL PRECISION CO., LIMITED					WEIGHT 1.0g
					SHEET 1/1
					REVISION A0

units:	mm
tolerance:	
X.X	±0.2mm
X.XX	±0.1mm
X.XXX	±0.05mm
UNSPECIFIED TOLERANCES	

DESCRIPTION

REVISIONS

www.xk-dg.cn www.helloxkb.com www.helloxkb.cn