

Circuit Diagram


NOTE:  
 1. Rating: AC125V 5A/250V 3A  
 2. Operating force: 30±10gf  
 3. Mechanical Life: 1,000,000  
 3. Electrical Life: 6000-10,000

ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK
①	Aluminum rivet	---	1	Aluminum Alloy	---	---
⑩	Spindle	---	1	Brass	Plating Nicke	---
⑨	Roller	---	1	Brass	Plating Nicke	---
⑧	Shrapnel 2	---	1	Copper Alloy	---	---
⑦	Shrapnel 1	---	1	Beryllium Copper	---	---
⑥	Contact	---	1	Copper Alloy	Plating silver	---
⑤	Lever	---	1	Stainess Steel	---	---
④	Terminal	---	3	Copper Alloy	Plating silver	---
③	Housing	---	1	PBT	Black	---
②	Knob	---	1	PBT	Black	---
①	Cover	---	1	PBT	Black	---

APPROVALS		DATE	TITLE:
DRAWN	J.X.Zhang	2014/7/21	MICRO SWITCHS
CHECKED			
APPROVALS			

APPROVALS		PART NO.	SCALE:
TOLERANCES ARE	30~110 ±	K9-1910F	1:1
	10~20 ±0.25		
	5~10 ±0.20		
	~5 ±0.20		

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			



ELECTRONICS CO.,LTD

MICRO SWITCHS

DRAWING NO. SHEET 1 OF 1