Product data sheet
Characteristics

H226AWK
Safety switch, heavy duty, fusible, 600A, 2 poles, 200 hp, 240 VAC/250 VDC, NEMA 12

Product availability : Non-Stock - Not normally stocked in distribution facility

Price* : 9,814.50 USD



Main

Product	Single Throw Safety Switch
Duty Rating	Heavy duty
Device application	Heavy application
Disconnect Type	Fusible disconnect
Factory Installed Neutral	None
Phase	3 phase
Number of Poles	2
Current Rating	600 A
Voltage Rating	250 V DC 240 V AC
Enclosure Rating	NEMA 3R/12 galvannealed steel
Maximum Horse Power Rating	75 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 200 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 50 hp 250 V at DC

Complementary

Short Circuit Current Rating	10 kA H or K 200 kA R, J or L
Fuse type	H or K R, J or L
Mounting Type	Surface
Electrical Connection	Lugs
Wiring configuration	2-wire
Wire Size	AWG 3/0...500 kcmil copper or aluminium
Tightening torque	375 lbf.in (42.37 N.m) AWG 3/0...500 kcmil)
Depth	10.13 in (257.30 mm)

* Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Width	26.25 in (666.75 mm)
Height	46.25 in (1174.75 mm)
Net Weight	175.05 lb(US) (79.4 kg)

Environment

Certifications	UL listed file E2875

Ordering and shipping details

Category	00155 - H&HU SW,NEMA12,400-1200A
Discount Schedule	DE1
GTIN	00785901450573
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

Contractual warranty

Warranty	18 months