

Crimping pliers - CRIMPFOX-SC 6L - 1212052

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Crimping pliers for non-isolated slip-on sleeves 2.8 mm, 4.8 mm and 6.3 mm, 0.5 - 6 mm², B crimp, with conduction

Why buy this product

- ☒ Marked die stations for precise processing of corresponding cross sections
- ☒ Consistently high crimping quality
- ☒ Unlockable pressure lock

Key commercial data

Packing unit	0
Minimum order quantity	1
Catalog page	Page 276 (CL2-2011)
GTIN	 4 046356 453943
Custom tariff number	82032000
Country of origin	SWEDEN

Technical data

General

Length (b)	256 mm
Height	68 mm
Width (a)	25 mm
Color	black
Weight	610 g
Die station	Crimping position 1
Min. cross section	0.5 mm ²
Max. cross section	1.5 mm ²
AWG min	22
AWG max	16
Die station	Crimping position 2
Min. cross section	1.5 mm ²
Max. cross section	2.5 mm ²
AWG min	16

Crimping pliers - CRIMPFOX-SC 6L - 1212052

Technical data

General

AWG max	14
Die station	Crimping position 3
Min. cross section	2.5 mm ²
Max. cross section	6 mm ²
AWG min	14
AWG max	10
Die station	Crimping position 4
Die station	Crimping position 5
Compression	B crimp
Type of contact	Slip-on sleeve

Classifications

eclass

eCl@ss 4.0	21040301
eCl@ss 4.1	21040301
eCl@ss 5.0	21040301
eCl@ss 5.1	21040301
eCl@ss 6.0	21043811
eCl@ss 7.0	21043811

etim

ETIM 2.0	EC001186
ETIM 3.0	EC001186
ETIM 4.0	EC001186

unspsc

UNSPSC 6.01	27112118
UNSPSC 7.0901	27111518
UNSPSC 11	23171604
UNSPSC 12.01	27111518
UNSPSC 13.2	27111518

Approvals

Approvals

Approvals

GOST

Ex Approvals

Crimping pliers - CRIMPFOX-SC 6L - 1212052

Approvals

Approvals submitted

Approval details



Accessories

Accessories

Tools

Replacement die - CRIMPFOX-SC 6/DIE - 1212051



Spare die for CRIMPFOX-SC 6

Replacement spring - CRIMPFOX/ SPR-1 - 1212069



Spare recuperating spring