



## MODULAR JACKS AND PLUGS: GLX Series

### Right Angle Modular Jack

#### Product Features

- 0.570" Height
- Snap-In Board Retention Tabs
- Available in 4, 6, 8 and 10 Position Housings
- CSA/NRTL Certified File No. LR78160
- UL File No. E134345

#### Performance Specifications

##### Materials and Finish

###### Housing Material

PBT Thermoplastic, UL 94V-0 Rated

###### Contact Material

Phosphor Bronze

#### Electrical Characteristics

##### Insulation Resistance

500 Megohms Min.

##### Dielectric Withstanding Voltage

1000V RMS, 60Hz

##### Contact Resistance

20 milliohms Max.

##### Current Rating

1.5A

##### Voltage Rating

125V DC

|                       |                     |                      |                  |
|-----------------------|---------------------|----------------------|------------------|
| 2D Drawing            | IGES                | STEP                 | 3D PDF           |
| Solder Profile        | CofC RoHS Compliant | CofC REACH Compliant | UL Plastic File  |
| Certificate of Origin | Check Stock         | Request a Sample     | Send Us An Email |

#### Generated Part Number



#### Part Number Builder

|                      |   |                      |                      |                      |
|----------------------|---|----------------------|----------------------|----------------------|
| <input type="text"/> | - | <input type="text"/> | <input type="text"/> | <input type="text"/> |
| Series               |   | Shield Option        | Positions & Contacts | Other Option         |

#### Series

GLX - Right Angle Modular Jack

#### Shield Options

- A - Non-Shielded with Panel Stops
- N - Non-Shielded without Panel Stops

#### Number of Positions / Contacts

- 44 - 4 Positions / 4 Contacts
- 64 - 6 Positions / 4 Contacts
- 66 - 6 Positions / 6 Contacts

#### Other Option

##### Plating Option

- Blank - Gold Flash
- 50 - 50µ" Gold Plating

#### Color Option

- Blank - Gray
- BLK - Black

Contact Kycon for High Temperature and Other Options

#### GLX Series

Dimensions in mm

#### GLX-A-44xx

