

ESD9FN3.3

List

List.....	1
Package outline.....	2
Features.....	2
Mechanical data.....	2
Maximum ratings	2
Electrical characteristics.....	2
Typical characteristics.....	3
Rating and characteristic curves.....	4
Pinning information.....	5
Marking.....	5
Suggested solder pad layout.....	5
Packing information.....	6
Reel packing.....	7
Suggested thermal profiles for soldering processes.....	7

ESD9FN3.3

72W Surface Mount TVS Uni-directional
For ESD Protection- 3.3V


Features

- Small body outline dimensions:
0.039" X 0.024" (1.0mm X 0.60mm).
- Halogen free.
- Provide transient protection:
IEC 61000-4-2 (ESD) Level 4
IEC 61000-4-4 (EFT) 80A (5/50ns)
IEC 61000-4-5 (Surge) (8/20us)
- Low leakage current.
- Suffix "-H" indicates Halogen-free parts, ex. ESD9FN3.3-H.


Mechanical data

- Epoxy: UL94-V0 rated flame retardant
- Case: Molded plastic, 0402
- Terminals: Golden Plated terminals,
solderable per MIL-STD-750, Method 2026
- Marking Code: Z
- Weight: Approximated 0.001gram

Schematic & Pin Configuration



Package outline



Maximum ratings (at $T_A=25^\circ\text{C}$ unless otherwise noted)

PARAMETER	CONDITIONS	Symbol	MIN.	TYP.	MAX.	UNIT
Peak pulse power	$t_p = 8/20\mu\text{s}$	P_{PP}			72	W
Peak pulse current	$t_p = 8/20\mu\text{s}$ (IEC 61000-4-5)	I_{PP}			6	A
ESD per IEC 61000-4-2	Air discharge	ESD			± 20	kV
	Contact discharge				± 15	
Operating junction temperature range		T_J	-55		+125	$^\circ\text{C}$
Storage temperature range		T_{STG}	-55		+150	$^\circ\text{C}$


Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

Electrical characteristics (at $T_A=25^\circ\text{C}$ unless otherwise noted, $V_F = 1.2\text{V Max.}$ @ $I_F = 10\text{mA}$)

Part No.	$V_{RWM}(V)$ Max.	$I_R(\mu A)$ @ V_{RWM} Max.	$I_T(mA)$	$V_{BR}(V)$ @ I_T Min.	$V_C(V)$ @ $I_{PP}=6A$ Max.	$C_J(pF)$ @ $V_R=0V, f=1\text{MHz}$ Typ.
ESD9FN3.3	3.3	3.0	1.0	5.0	12	45

Over voltage available upon request.

1. V_{BR} is measured with a pulse test current I_T at an ambient temperature of 25°C .
2. Surge current waveform per Figure 1.

ESD9FN3.3**Typical characteristics** (at $T_A=25^\circ\text{C}$ unless otherwise noted)

Uni-Directional TVS

 V_C : Clamping Voltage @ I_{PP} I_{PP} : Maximum Reverse Peak Pulse Current V_{RWM} : Maximum Reverse Working voltage I_R : Maximum Reverse Leakage Current @ V_{RWM} V_{BR} : Breakdown voltage @ I_T I_T : Test Current P_{PP} : Peak Pulse Power I_F : Forward Current V_F : Forward Voltage @ I_F C_J : Typ. Capacitance @ $V_R = 0\text{V}$ and $f = 1\text{MHz}$

Rating and characteristic curves (ESD9FN3.3)

FIG.1- 8 X 20us PULSE WAVEFORM




FIG.2- POWER RATING DERATING CURVE





FIG.3- TERMINALS CHARACTERISTICS




ESD9FN3.3


Pinning information

Pin	Simplified outline	Symbol
Pin1 cathode Pin2 anode		

Marking

Type number	Marking code	Example
ESD9FN3.3	Z	

Suggested solder pad layout




Dimensions in inches and (millimeters)

PACKAGE	A	B	C
0402	0.028 (0.70)	0.020 (0.50)	0.010 (0.25)

ESD9FN3.3

Packing information



unit:mm

Item	Symbol	Tolerance	0402
Carrier width	A	0.05	0.74
Carrier length	B	0.05	1.17
Carrier depth	C	0.05	0.62
Sprocket hole	d	0.1	1.50
13" Reel outside diameter	D	2.0	-
13" Reel inner diameter	D ₁	min	-
7" Reel outside diameter	D	2.0	178.00
7" Reel inner diameter	D ₁	min	62.00
Feed hole diameter	D ₂	0.5	13.00
Sprocket hole position	E	0.1	1.75
Punch hole position	F	0.1	3.50
Punch hole pitch	P	0.1	2.00
Sprocket hole pitch	P ₀	0.1	4.00
Embossment center	P ₁	0.1	2.00
Overall tape thickness	T	0.1	0.23
Tape width	W	0.3	8.00
Reel width	W ₁	1.0	11.40

Note: Devices are packed in accordance with EIA standard RS-481-A and specifications listed above.


ESD9FN3.3

Reel packing

PACKAGE	REEL SIZE	REEL (pcs)	COMPONENT SPACING (m/m)	BOX (pcs)	INNER BOX (m/m)	REEL DIA, (m/m)	CARTON SIZE (m/m)	CARTON (pcs)	APPROX. GROSS WEIGHT (kg)
0402	7"	10,000	2.0	100,000	183*123*183	178	382*257*387	800,000	8.5

Suggested thermal profiles for soldering processes

- 1.Storage environment: Temperature=5°C~40°C Humidity=55%±25%
- 2.Reflow soldering of surface-mount devices



3.Reflow soldering

Profile Feature	Soldering Condition
Average ramp-up rate(T _L to T _P)	<3°C/sec
Preheat -Temperature Min(T _{smin}) -Temperature Max(T _{smax}) -Time(min to max)(t _s)	150°C 200°C 60~120sec
T _{smax} to T _L -Ramp-upRate	<3°C/sec
Time maintained above: -Temperature(T _L) -Time(t _L)	217°C 60~260sec
Peak Temperature(T _P)	255°C-0/+5°C
Time within 5°C of actual Peak Temperature(t _P)	10~30sec
Ramp-down Rate	<6°C/sec
Time 25°C to Peak Temperature	<6minutes