

# BC817-16 THRU BC817-40

## NPN Small Signal Transistor 310mW

### Features

- Halogen free available upon request by adding suffix "-HF"
- Lead Free Finish/RoHS Compliant ("P" Suffix designates RoHS Compliant. See ordering information)
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Ideally Suited for Automatic Insertion
- 150 C Junction Temperature
- For Switching and AF Amplifier Applications
- Epitaxial Planar Die Construction

### Mechanical Data

- Case: SOT-23, Molded Plastic
- Terminals: Solderable per MIL-STD-202, Method 208
- Polarity: See Diagram
- Weight: 0.008 grams ( approx.)
- Marking: BC817-16            6A  
                                           BC817-25            6B  
                                           BC817-40            6C

### Maximum Ratings @ 25°C Unless Otherwise Specified

| Charateristic                                     | Symbol         | Value   | Unit |
|---------------------------------------------------|----------------|---------|------|
| Collector-Emitter Voltage                         | $V_{CEO}$      | 45      | V    |
| Emitter-Base Voltage                              | $V_{EBO}$      | 5       | V    |
| Collector Current                                 | $I_C$          | 500     | mA   |
| Peak Collector Current                            | $I_{CM}$       | 1000    | mA   |
| Peak Emitter Current                              | $I_{EM}$       | 1000    | mA   |
| Power Dissipation@ $T_s=50^\circ\text{C}$ (Note1) | $P_d$          | 300     | mW   |
| Operating & Storage Temperature                   | $T_j, T_{STG}$ | -55~150 | °C   |

**Note:** 1. Device mounted on Ceramic Substrate 0.7mm X 2.5cm<sup>2</sup> area

### SOT-23

| DIMENSIONS |        |       |      |      |      |
|------------|--------|-------|------|------|------|
| DIM        | INCHES |       | MM   |      | NOTE |
|            | MIN    | MAX   | MIN  | MAX  |      |
| A          | .110   | .120  | 2.80 | 3.04 |      |
| B          | .083   | .104  | 2.10 | 2.64 |      |
| C          | .047   | .055  | 1.20 | 1.40 |      |
| D          | .035   | .041  | .89  | 1.03 |      |
| E          | .070   | .081  | 1.78 | 2.05 |      |
| F          | .018   | .024  | .45  | .60  |      |
| G          | .0005  | .0039 | .013 | .100 |      |
| H          | .035   | .044  | .89  | 1.12 |      |
| J          | .003   | .007  | .085 | .180 |      |
| K          | .015   | .020  | .37  | .51  |      |

**Suggested Solder Pad Layout**

## Electrical Characteristics @25°C unless otherwise specified

| Parameter                            | Symbol        | Test conditions                           | Min | Typ | Max | Unit    |
|--------------------------------------|---------------|-------------------------------------------|-----|-----|-----|---------|
| Collector-base breakdown voltage     | $V_{CBO}$     | $I_C = 10\mu A, I_E = 0$                  | 50  |     |     | V       |
| Collector-emitter breakdown voltage  | $V_{CEO}$     | $I_C = 10mA, I_B = 0$                     | 45  |     |     | V       |
| Emitter-base breakdown voltage       | $V_{EBO}$     | $I_E = 1\mu A, I_C = 0$                   | 5   |     |     | V       |
| Collector cut-off current            | $I_{CBO}$     | $V_{CB} = 45V, I_E = 0$                   |     |     | 0.1 | $\mu A$ |
| Emitter cut-off current              | $I_{EBO}$     | $V_{EB} = 4V, I_C = 0$                    |     |     | 0.1 | $\mu A$ |
| DC current gain                      | $h_{FE(1)}$   | $V_{CE} = 1V, I_C = 100mA$                | 100 |     | 600 |         |
|                                      | $h_{FE(2)}$   | $V_{CE} = 1V, I_C = 500mA$                | 40  |     |     |         |
| Collector-emitter saturation voltage | $V_{CE(sat)}$ | $I_C = 500mA, I_B = 50mA$                 |     |     | 0.7 | V       |
| Base-emitter saturation voltage      | $V_{BE(sat)}$ | $I_C = 500mA, I_B = 50mA$                 |     |     | 1.2 | V       |
| Base-emitter voltage                 | $V_{BE}$      | $V_{CE} = 1V, I_C = 500mA$                |     |     | 1.2 | V       |
| Collector capacitance                | $C_{ob}$      | $V_{CB} = 10V, f = 1MHz$                  |     | 10  |     | pF      |
| Transition frequency                 | $f_T$         | $V_{CE} = 5V, I_C = 10mA$<br>$f = 100MHz$ | 100 |     |     | MHz     |

### CLASSIFICATION OF $h_{FE(1)}$

| Rank  | BC817-16 | BC817-25 | BC817-40 |
|-------|----------|----------|----------|
| Range | 100-250  | 160-400  | 250-600  |




Fig. 1, Power Derating Curve




Fig. 2, Gain-Bandwidth Product vs Collector Current




Fig. 3, Collector Sat. Voltage vs Collector Current




Fig. 4, DC Current Gain vs Collector Current




Fig. 5, Typical Emitter-Collector Characteristics




Fig. 6, Typical Emitter-Collector Characteristics



Micro Commercial Components

### Ordering Information :

| Device         | Packing               |
|----------------|-----------------------|
| Part Number-TP | Tape&Reel; 3Kpcs/Reel |

Note : Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

#### \*\*\*IMPORTANT NOTICE\*\*\*

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

#### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

#### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

[www.mccsemi.com](http://www.mccsemi.com)