Adapter
FSP025-DHAN2

DESCRIPTION
This product is a 25 watts AC to DC power supply intended for use in IPC systems that has a small wattage demands. This adapter operates at 90 to 264 VAC input voltage. The unit meets EN55022, EN55024 and FCC class B emission limits, and is designed for ITE application.



APPLICATION
Industrial Application

FEATURES
- Meet Energy Star EPS2.0/ErP lot 7
- Meet DOE Level VI
- High Altitude 5,000M
- High Reliability
- EMC Standard: EN55022 CLASS B / EN55024 CLASS B
- Over Current Protection
- Over Temperature Protection
- Over Voltage Protection

WATTAGE
Wattage:	25W

PRODUCT HIGHLIGHT
V-Output:	12V
O/P Current:	2.08A
Socket Type:	C14

INPUT ELECTRICAL
Input Voltage:	90 ~ 264 V
Input Frequency:	47 ~ 63 Hz

OUTPUT ELECTRICAL
Single Output:	12 V/ 2.08 A

SAFETY STANDARD APPAOVAL

NO LOAD AND EFFICIENCY
No Load:	0.1 Watts

PROTECTION
Protection:	OVP,OCP,OTP

ENVIRONMENTAL REQUIREMENTS
TEMP. Range:	Storage : -25 to + 80 ℃
Altitude :	5000 M
MTBF:	200,000 hours at typical load at 25℃ ambient base on SR332

MECHANICAL
Dimension:	94mm(L) x 38.4mm(W) x 29.6mm(H)
LED Indicator:	No
On/ Off Switch:	No

This content is subject to change, please refer to specification for more detail.
FSP reserve the right to change the content without prior notice