Product data sheet
Characteristics

AP7750A
Rack ATS, 100-120V, 15A, 5-15P In, (10) 5-15R Out



Commercial status
This Product is Obsolete : DEC 02, 2020

⚠ This Product is Obsolete

Overview

Lead time	Usually in Stock

General

Provided Equipment	Rack Mounting brackets User Manual

Physical

Cable length	8 Ft (2.44 m)
Color	Black
Depth	9.29 In (23.6 cm)
Height	1.73 In (4.4 cm)
Product Weight	10.36 Lb(US) (4.7 kg)
Width	17.01 In (43.2 cm)

Input

Input Frequency	50/60 Hz
Line Rated Current	12 A
Plug standard	NEMA 5-15P
Permissible voltage	100…125 V
Input current limits	15 A
Load Capacity	1440 VA
Nominal Input Voltage	100 V 120 V

Output

Max current draw	15 A
Number of power socket outlets	10 NEMA 5-15R
Output voltage	100 V 120 V

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Conformance

Product Certifications	PSE TÜV-C TÜV-NURTL VCCI Class A
Standards	FCC Part 15 class A ICES-003

Environmental

Ambient Air Temperature for Operation	23…113 °F (-5…45 °C)
Relative Humidity	0…95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13…149 °F (-25…65 °C)
Storage Relative Humidity	0…95 %
Storage altitude	0…50000 Ft (0.00…15240.00 m)

Ordering and shipping details

GTIN	00731304299899
Package weight(Lbs)	14.29 Lb(US) (6.48 kg)

Packing Units

Package 1 Height	2.76 In (7 cm)
Package 1 width	19.13 In (48.6 cm)
Package 1 Length	13.50 In (34.3 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
Mercury free	Yes
RoHS exemption information	Yes
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace

Product Life Status : Post commercialisation

AP7750A may be replaced by any of the following products:



AP4450

Rack ATS, 100/120V, 15A, 5-15 in, (10) 5-15R out

Qty 1

Substitution date: | Migration SPD