OptiChannel
Indoor Distribution Cable

Riser

Features

- E-Z Strip Buffer For Contractor-Friendly Termination
- Compact Cable Diameter Reduces Pathway Congestion
- Premium Bend-Insensitive Fiber For Enhanced Optical Performance

Ordering Information

Description	Fiber Type	Catalog No.	UPC No.
Indoor Tight Buffer Distribution, 24 Fiber, Riser, Orange	OM1 Multimode	**HFCD1024R6**	662620246970

Listings

ANSI/ICEA S-83-596
TIA-568.3-D
NFPA-262/UL910/CSA FT-6
Telcordia GR-409 and GR-20

Specifications

Fiber Coating	900 Micron PVC Tight Buffer
Cable Diameter in (mm)	0.32 (8.1)
Cable Weight (lb/kft)	43
Construction	Single Unit, Aramid Strength Member
Armor	None

Performance

Cable Attenuation (dB/km at 850/1300 nm)

3.5/1.5

Maximum Installation Pulling Load (lb)

198

Maximum Operating Temperature

-4°F to +158°F (-20°C to +70°C)

Minimum Bend Radius, In-Service in (cm)

3.2 (8.1)

Accessories

Fiber Strip Tool	**OFSTRIP2**
Splice Tray, 12 Fusion	**STRAY12F**
Splice Tray, 24 Fusion	**STRAY24F**
Splice Protection Sleeves	**FSHST401025**

Online Resources

eCatalog