

## General Description

The EC95808 series are highly accurate, ultra-low current consumption voltage detectors, developed by CMOS process. Two output forms N-channel open-drain and CMOS output are available. The device is ideal for battery powered portable devices which require low current consumption.

The EC95808 consists of a comparator, a voltage reference unit, a resistor divider, an output driver, and a hysteresis circuit. The detection voltage is fixed internally with  $\pm 2.0\%$  accuracy by advanced trimming technology.

The devices are available in SOT23-3L, SC82-4L and SC70-3L packages.


## Features

- Ultra-Low Quiescent Current 1.0  $\mu\text{A}$  (Typ.)
- High Accuracy of Detection Voltage  $\pm 2\%$
- Hysteresis Width 5% VDET (Typ.)
- Detection Voltage 1.6V to 6.0V (0.1V Step)
- Operating Voltage Range 1.5V to 6.0V
- N-ch Open Drain and CMOS Output
- SOT23-3L, SC82-4L and SC70-3L Packages
- RoHS Compliant and 100% Lead (Pb)-Free and Green (Halogen Free with Commercial Standard)


## Applications

- Microprocessor Reset Circuitry
- Memory Battery Back-up Circuits
- Power-on Reset Circuits
- Power Failure Detection
- System Battery Life and Charge Voltage Monitors





## Typical Application Circuit




## Ordering Information




## Pin Description

| Part NO.                                                                                                                        | Part NO.                         | Pin | Symbol    | Pin Description       |
|---------------------------------------------------------------------------------------------------------------------------------|----------------------------------|-----|-----------|-----------------------|
|  <p>(Top View)</p> <p>SOT23-3L</p>             | EC95808NXXB1NR<br>EC95808CXXB1NR | 1   | $V_{OUT}$ | Regulator Output Pin. |
|                                                                                                                                 |                                  | 2   | GND       | Ground Pin.           |
|                                                                                                                                 |                                  | 3   | $V_{IN}$  | Regulator Input Pin.  |
|  <p>(Top View)</p> <p>SC82-4L(Pin Type I)</p>  | EC95808NXXC7IR<br>EC95808CXXC7IR | 1   | $V_{OUT}$ | Regulator Output Pin. |
|                                                                                                                                 |                                  | 2   | $V_{IN}$  | Regulator Input Pin.  |
|                                                                                                                                 |                                  | 3   | NC        | No Connect            |
|                                                                                                                                 |                                  | 4   | GND       | Ground Pin.           |
|  <p>(Top View)</p> <p>SC82-4L(Pin Type S)</p> | EC95808NXXC7SR<br>EC95808CXXC7SR | 1   | $V_{OUT}$ | Regulator Output Pin. |
|                                                                                                                                 |                                  | 2   | $V_{IN}$  | Regulator Input Pin.  |
|                                                                                                                                 |                                  | 3   | NC        | No Connect            |
|                                                                                                                                 |                                  | 4   | GND       | Ground Pin.           |
|  <p>(Top View)</p> <p>SC70-3L</p>            | EC95808NXXC1NR<br>EC95808CXXC1NR | 1   | GND       | Ground Pin.           |
|                                                                                                                                 |                                  | 2   | $V_{OUT}$ | Regulator Output Pin. |
|                                                                                                                                 |                                  | 3   | $V_{IN}$  | Regulator Input Pin.  |


## Marking Information




SOT-23  
(Top View)



SC-82 (I)  
(Top View)



SC-82 (S)  
(Top View)



SC-70  
(Top View)

① Represents Products Series(See Note1)

| Mark | Vout Type | Voltage(V) | Mark | Vout Type | Voltage(V) |
|------|-----------|------------|------|-----------|------------|
| A    | CMOS      | 0.X        | H    | N-ch      | 0.X        |
| B    | CMOS      | 1.X        | J    | N-ch      | 1.X        |
| C    | CMOS      | 2.X        | K    | N-ch      | 2.X        |
| D    | CMOS      | 3.X        | L    | N-ch      | 3.X        |
| E    | CMOS      | 4.X        | M    | N-ch      | 4.X        |
| F    | CMOS      | 5.X        | N    | N-ch      | 5.X        |
| G    | CMOS      | 6.X        | P    | N-ch      | 6.X        |

② Represents decimal number of detect voltage(See Note 2)

| Mark | Voltage(V) | Mark | Voltage(V) |
|------|------------|------|------------|
| 0    | X.0        | 5    | X.5        |
| 1    | X.1        | 6    | X.6        |
| 2    | X.2        | 7    | X.7        |
| 3    | X.3        | 8    | X.8        |
| 4    | X.4        | 9    | X.9        |

③ 、 ④ Represents Production Date Code

Note :

- \* There are two under-lines on 4<sup>th</sup> & 5<sup>th</sup> digit for Green package.
- \* There are no under-lines on 4<sup>th</sup> & 5<sup>th</sup> digit for Pb-Free package.

## Absolute Maximum Rating

| Parameter                            |          | Symbol           | Ratings                   | Units |
|--------------------------------------|----------|------------------|---------------------------|-------|
| Input Voltage V <sub>IN</sub> to GND |          | V <sub>IN</sub>  | 6.0                       | V     |
| Output Voltage, CMOS                 |          | V <sub>OUT</sub> | GND~V <sub>IN</sub> +0.3V | V     |
| Output Voltage, N-ch                 |          |                  | GND~6V                    |       |
| Output Current                       |          | I <sub>OUT</sub> | 50                        | mA    |
| Junction Temperature                 |          | T <sub>J</sub>   | +155                      | ℃     |
| Power Dissipation                    | SOT23-3L | P <sub>D</sub>   | 310                       | mW    |
|                                      | SC82-4L  |                  | 250                       |       |
|                                      | SC70-3L  |                  | 250                       |       |
| Operating Ambient Temperature        |          | T <sub>OPR</sub> | -40 ~ +85                 | ℃     |
| Storage Temperature                  |          | T <sub>STG</sub> | -55 ~ +150                | ℃     |
| Lead Temperature (soldering, 10sec)  |          |                  | +260                      | ℃     |

Note :

\* The power dissipation values are based on the condition that junction temperature  $T_J$  and ambient temperature  $T_A$  difference is 100°C.


\* Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device.

These are stress ratings only, and function operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum -rated conditions for extended periods may affect device reliability.


## Electrical Characteristics( $T_A=25^\circ\text{C}$ , unless otherwise noted.)

| Symbol     | Parameter               | Test Conditions                               |             | Min                 | Typ                 | Max                 | Unit       |
|------------|-------------------------|-----------------------------------------------|-------------|---------------------|---------------------|---------------------|------------|
| $V_{IN}$   | Operating Voltage       |                                               |             | 1.5                 |                     | 6.0                 | V          |
| $V_{DET}$  | Detection Voltage       |                                               |             | $V_{DET}^*$<br>0.98 | $V_{DET}$           | $V_{DET}^*$<br>1.02 | V          |
| $V_{HYS}$  | Hysteresis Width        |                                               |             | $V_{DET}^*$<br>0.03 | $V_{DET}^*$<br>0.05 | $V_{DET}^*$<br>0.08 | V          |
| $I_Q$      | Quiescent Current       | $V_{IN}=5V$                                   |             |                     | 1.0                 | 3.0                 | μA         |
| $I_{OUT}$  | Output Current          | N-ch<br>Output                                | $V_{IN}=2V$ | 3                   | 7                   |                     | mA         |
|            |                         |                                               | $V_{IN}=3V$ | 5                   | 10                  |                     |            |
|            |                         |                                               | $V_{IN}=5V$ | 7                   | 13                  |                     |            |
| $I_{LEAK}$ | Leakage Current         | N-ch, $V_{IN}=V_{OUT}=5V$                     |             |                     |                     | 0.1                 | μA         |
| $T_C$      | Temperature Coefficient | $-40^\circ\text{C} < T_A < +85^\circ\text{C}$ |             |                     | 100                 | 350                 | ppm/<br>°C |
|            | Response Time           |                                               |             |                     |                     | 200                 | μS         |

### Function Block Diagram



CMOS Output




N-ch Open drain Output


## Typical Operating Characteristics

(EC95808C22C7IR tested,  $T_A = +25^\circ\text{C}$ , unless otherwise noted.)


### (1) Output Voltage vs. Input Voltage




### (2) Supply Current v.s Input Voltage




### (3) Detect Voltage v.s Ambient Temperature




### (4) Supply Current v.s Ambient Temperature



(5) Start-up Voltage Waveform




(6) Shutdown Voltage Waveform



## Detail Description

### Basic Operation

For EC95808C CMOS Active low output:



- (1) When the input voltage  $V_{IN}$  is higher than the release voltage  $V_{REL}$  ( $V_{REL} = V_{DET} + V_{HYS}$ ), the N-ch MOS is OFF and P-ch MOS is ON to provide  $V_{IN}$  at the output. Since NMOS is OFF, the comparator input voltage is

$$V_{IN} \times (R_2 + R_3) / (R_1 + R_2 + R_3)$$


When the  $V_{IN}$  goes below the  $V_{REL}$ ,  $V_{IN}$  keeps at the output since  $V_{IN}$  remains above the detection voltage  $V_{DET}$ . The difference between  $V_{REL}$  and  $V_{DET}$  is the hysteresis range.

- (2) When the  $V_{IN}$  goes below the  $V_{DET}$ , the N-ch MOS is ON and P-ch MOS is OFF to provide GND level at the output. At this time NMOS is ON, the comparator input voltage is

$$V_{IN} \times R_2 / (R_1 + R_2)$$

- (3) When the  $V_{IN}$  falls below the minimum operating voltage, the output becomes undefined changed to  $V_{IN}$  if the output is pulled up to  $V_{IN}$ .

- (4) When the  $V_{IN}$  rises above the minimum operating voltage, the GND level appears at the output. The GND level keeps at the output even when  $V_{IN}$  goes above the detection voltage  $V_{DET}$ , as long as it doesn't exceed the release voltage  $V_{REL}$ .




(5) When the  $V_{IN}$  rises above the release voltage  $V_{REL}$ , the N-ch MOS is OFF and P-ch MOS is ON to provide  $V_{IN}$  at the output.

### Oscillation Notice


When a resistor is connected between the input voltage and the input pin  $V_{IN}$  with CMOS output configuration, oscillation may occur due to voltage drop at  $R_{IN}$ . The voltage drop is

$$V_{DROP} = R_{IN} \times I_{OUT}$$



When the  $V_{IN}$  input voltage rises above the release voltage, the detector output voltage increases and the load current  $I_{OUT}$  will flow at  $R_{LOAD}$ . A voltage drop is produced at  $R_{IN}$ . The voltage drop will also lead to a fall in the input voltage at  $V_{IN}$  pin. When the  $V_{IN}$  input voltage falls below the detection voltage, output voltage falls to GND and the output current will cease. Then the voltage drop at  $R_{IN}$  will disappear, and the  $V_{IN}$  input voltage will rise to commence release operation. Oscillation may occur with this release detection-release repetition. It's recommended not to use the CMOS configuration when a resistor  $R_{IN}$  is connected between  $V_{IN}$  input pin and the power source. Please use N-channel open drain configuration when  $R_{IN}$  is required.

## Power-on Reset Circuit




A power-on reset circuit example using EC95808N is shown in the figure. Resistor R should be 75 kΩ or less to avoid oscillation. Diode D instantaneously discharges the charge stored in the capacitor C at the power falling. Diode D can be removed when the delay of the falling time is not important.



## Change of Detection Voltage

For EC95808N N-channel open drain output configuration, the detection voltage can be changed with resistance dividers as shown in the figure.




Detection voltage is changed to

$$V_{DET} \times (R1+R2) / R2$$

Hysteresis width is also changed to

$$V_{HYS} \times (R1+R2) / R2$$

Resistor R1 should be 75 kΩ or less to avoid oscillation. The detection voltage can also be changed with diodes as shown in the figure.




Detection voltage becomes



$$V_{F1} + V_{F2} + V_{DET}$$

## Mechanical Dimensions

### OUTLINE DRAWING SOT23-3L




| Symbols | Dimensions in Millimeters |           |       |
|---------|---------------------------|-----------|-------|
|         | Min                       | Nom       | Max   |
| A       | 1.00                      | 1.10      | 1.40  |
| A1      | 0.00                      | 0.05      | 0.10  |
| A2      | 1.00                      | 1.10      | 1.30  |
| A3      | 0.70                      | 0.80      | 0.90  |
| b       | 0.35                      | 0.40      | 0.50  |
| C       | 0.12                      | 0.125     | 0.225 |
| D       | 2.70                      | 2.90      | 3.10  |
| E       | 2.60                      | 2.80      | 3.00  |
| E1      | 1.40                      | 1.60      | 1.80  |
| e       | ---                       | 0.95(Typ) | ---   |
| e1      | ---                       | 1.90(Typ) | ---   |
| θ1      | 1°                        | 5°        | 9°    |
| L       | 0.37                      | ---       | ---   |
| L1      | ---                       | 0.6REF    | ---   |
| L1-L2   | ---                       | ---       | 0.12  |



## Mechanical Dimensions


### OUTLINE DRAWING SC82-4L(Pin Type I)



| Symbols    | Dimension in millimeters |      |      | Dimension in inches |       |       |
|------------|--------------------------|------|------|---------------------|-------|-------|
|            | Min                      | Nom  | Max  | Min                 | Nom   | Max   |
| A          | 0.80                     | ---  | 1.10 | 0.031               | ---   | 0.043 |
| A1         | 0.00                     | ---  | 0.10 | 0.000               | ---   | 0.004 |
| A2         | 0.70                     | 0.90 | 1.00 | 0.027               | 0.035 | 0.039 |
| b          | 0.25                     | 0.30 | 0.40 | 0.010               | 0.012 | 0.016 |
| b1         | 0.35                     | 0.40 | 0.50 | 0.014               | 0.016 | 0.020 |
| C          | 0.10                     | ---  | 0.26 | 0.004               | ---   | 0.010 |
| D          | 1.80                     | 2.00 | 2.20 | 0.071               | 0.079 | 0.087 |
| E1         | 1.15                     | 1.25 | 1.35 | 0.045               | 0.049 | 0.053 |
| E          | 1.80                     | 2.10 | 2.40 | 0.071               | 0.083 | 0.094 |
| e          | ---                      | 1.30 | ---  | ---                 | 0.051 | ---   |
| L          | 0.26                     | 0.36 | 0.46 | 0.010               | 0.014 | 0.018 |
| L2         | ---                      | 0.15 | ---  | ---                 | 0.006 | ---   |
| y          | ---                      | ---  | 0.10 | ---                 | ---   | 0.004 |
| $\theta$   | 0°                       | ---  | 8°   | 0°                  | ---   | 8°    |
| $\theta$ 1 | 4°                       | ---  | 12°  | 4°                  | ---   | 12°   |


### Mechanical Dimensions

#### OUTLINE DRAWING SC82-4L(Pin Type S)



| Symbols    | Dimension in millimeters |      |      | Dimension in inches |       |       |
|------------|--------------------------|------|------|---------------------|-------|-------|
|            | Min                      | Nom  | Max  | Min                 | Nom   | Max   |
| A          | 0.80                     | ---  | 1.10 | 0.031               | ---   | 0.043 |
| A1         | 0.00                     | ---  | 0.10 | 0.000               | ---   | 0.004 |
| A2         | 0.70                     | 0.90 | 1.00 | 0.027               | 0.035 | 0.039 |
| b          | 0.25                     | 0.30 | 0.40 | 0.010               | 0.012 | 0.016 |
| b1         | 0.35                     | 0.40 | 0.50 | 0.014               | 0.016 | 0.020 |
| C          | 0.10                     | ---  | 0.26 | 0.004               | ---   | 0.010 |
| D          | 1.80                     | 2.00 | 2.20 | 0.071               | 0.079 | 0.087 |
| E1         | 1.15                     | 1.25 | 1.35 | 0.045               | 0.049 | 0.053 |
| E          | 1.80                     | 2.10 | 2.40 | 0.071               | 0.083 | 0.094 |
| e          | ---                      | 1.30 | ---  | ---                 | 0.051 | ---   |
| L          | 0.26                     | 0.36 | 0.46 | 0.010               | 0.014 | 0.018 |
| L2         | ---                      | 0.15 | ---  | ---                 | 0.006 | ---   |
| y          | ---                      | ---  | 0.10 | ---                 | ---   | 0.004 |
| $\theta$   | 0°                       | ---  | 8°   | 0°                  | ---   | 8°    |
| $\theta_1$ | 4°                       | ---  | 12°  | 4°                  | ---   | 12°   |

### Mechanical Dimensions OUTLINE DRAWING SC70-3L



| Symbols | Dimensions in millimeters |      |      | Dimensions in millimeters |       |       |
|---------|---------------------------|------|------|---------------------------|-------|-------|
|         | Min                       | Nom  | Max  | Min                       | Nom   | Max   |
| A       | 0.80                      | ---  | 1.10 | 0.031                     | ---   | 0.043 |
| A1      | 0.00                      | ---  | 0.10 | 0.000                     | ---   | 0.004 |
| A2      | 0.70                      | 0.90 | 1.00 | 0.028                     | 0.035 | 0.039 |
| b       | 0.25                      | ---  | 0.40 | 0.010                     | ---   | 0.016 |
| C       | 0.08                      | ---  | 0.22 | 0.003                     | ---   | 0.009 |
| D       | 1.80                      | 2.00 | 2.20 | 0.071                     | 0.079 | 0.087 |
| E       | 1.80                      | 2.10 | 2.40 | 0.071                     | 0.083 | 0.094 |
| E1      | 1.16                      | 1.26 | 1.35 | 0.045                     | 0.049 | 0.053 |
| e       | ---                       | 1.30 | ---  | ---                       | 0.051 | ---   |
| L       | 0.26                      | 0.36 | 0.46 | 0.010                     | 0.014 | 0.018 |
| L2      | ---                       | 0.15 | ---  | ---                       | 0.006 | ---   |
| y       | ---                       | ---  | 0.10 | ---                       | ---   | 0.004 |
| θ       | 0°                        | 4°   | 8°   | 0°                        | 4°    | 8°    |
| θ1      | 4°                        | ---  | 12°  | 4°                        | ---   | 12°   |