# Printed-circuit board connector - IC 2,5/ 6-STF-5,08 BK - 1763711

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Plug component, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 6, Pitch: 5.08 mm, Connection method: Screw connection, Color: black, Contact surface: Tin

## Key commercial data

| | |
|---|---|
| Packing unit | 1 pc |
| Minimum order quantity | 50 pc |
| Weight per Piece (excluding packing) | 11.2 GRM |
| Custom tariff number | 85366990 |
| Country of origin | Germany |

## Technical data

### Dimensions

| | |
|---|---|
| Pitch | 5.08 mm |
| Dimension a | 25.4 mm |

### General

| | |
|---|---|
| Range of articles | IC 2,5/..-STF |
| Insulating material group | I |
| Rated surge voltage (III/3) | 4 kV |
| Rated surge voltage (III/2) | 4 kV |
| Rated surge voltage (II/2) | 4 kV |
| Rated voltage (III/3) | 250 V |
| Rated voltage (III/2) | 320 V |
| Rated voltage (II/2) | 630 V |
| Connection in acc. with standard | EN-VDE |
| Nominal current $I_N$ | 12 A |
| Nominal cross section | 2.5 mm² |
| Maximum load current | 12 A |
| Insulating material | PA |
| Inflammability class according to UL 94 | V0 |
| Number of positions | 6 |

### Connection data

| | |
|---|---|
| Conductor cross section solid min. | 0.2 mm² |
| Conductor cross section solid max. | 2.5 mm² |

# Printed-circuit board connector - IC 2,5/ 6-STF-5,08 BK - 1763711

## Technical data

### Connection data

| | |
|---|---|
| Conductor cross section stranded min. | 0.2 mm² |
| Conductor cross section stranded max. | 2.5 mm² |
| Conductor cross section stranded, with ferrule without plastic sleeve min. | 0.25 mm² |
| Conductor cross section stranded, with ferrule without plastic sleeve max. | 2.5 mm² |
| Conductor cross section stranded, with ferrule with plastic sleeve min. | 0.25 mm² |
| Conductor cross section stranded, with ferrule with plastic sleeve max. | 2.5 mm² |
| Conductor cross section AWG/kcmil min. | 24 |
| Conductor cross section AWG/kcmil max | 12 |
| 2 conductors with same cross section, solid min. | 0.2 mm² |
| 2 conductors with same cross section, solid max. | 1 mm² |
| 2 conductors with same cross section, stranded min. | 0.2 mm² |
| 2 conductors with same cross section, stranded max. | 1.5 mm² |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, min. | 0.25 mm² |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, max. | 1 mm² |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. | 0.5 mm² |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. | 1.5 mm² |
| Minimum AWG according to UL/CUL | 30 |
| Maximum AWG according to UL/CUL | 12 |

## Classifications

### eCl@ss

| | |
|---|---|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 27260701 |
| eCl@ss 5.0 | 27260701 |
| eCl@ss 5.1 | 27260701 |
| eCl@ss 6.0 | 27260704 |
| eCl@ss 7.0 | 27440402 |
| eCl@ss 8.0 | 27440402 |

### ETIM

| | |
|---|---|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC002638 |
| ETIM 5.0 | EC002638 |

# Printed-circuit board connector - IC 2,5/ 6-STF-5,08 BK - 1763711

## Classifications

### UNSPSC

| | |
|---|---|
| UNSPSC 6.01 | 30211810 |
| UNSPSC 7.0901 | 39121409 |
| UNSPSC 11 | 39121409 |
| UNSPSC 12.01 | 39121409 |
| UNSPSC 13.2 | 39121409 |

## Approvals

### Approvals

Approvals

CSA / UL Recognized / VDE Gutachten mit Fertigungsüberwachung / cUL Recognized / GOST / IECEE CB Scheme / GOST / CCA / cULus Recognized

Ex Approvals

Approvals submitted

### Approval details

CSA

| | B | D |
|---|---|---|
| mm²/AWG/kcmil | 28-12 | 28-12 |
| Nominal current IN | 10 A | 10 A |
| Nominal voltage UN | 300 V | 300 V |

UL Recognized

| | B | D |
|---|---|---|
| mm²/AWG/kcmil | 30-12 | 30-12 |
| Nominal current IN | 12 A | 10 A |
| Nominal voltage UN | 250 V | 300 V |

# Printed-circuit board connector - IC 2,5/ 6-STF-5,08 BK - 1763711

## Approvals

VDE Gutachten mit Fertigungsüberwachung

| | |
|---|---|
| mm²/AWG/kcmil | 0.2-2.5 |
| Nominal current IN | 12 A |
| Nominal voltage UN | 250 V |

cUL Recognized

| | B | D |
|---|---|---|
| mm²/AWG/kcmil | 30-12 | 30-12 |
| Nominal current IN | 12 A | 10 A |
| Nominal voltage UN | 250 V | 300 V |

GOST

IECEE CB Scheme

| | |
|---|---|
| mm²/AWG/kcmil | 0.2-2.5 |
| Nominal current IN | 12 A |
| Nominal voltage UN | 250 V |

GOST

CCA

| | |
|---|---|
| mm²/AWG/kcmil | 0.2-2.5 |
| Nominal current IN | 12 A |
| Nominal voltage UN | 250 V |

# Printed-circuit board connector - IC 2,5/ 6-STF-5,08 BK - 1763711

## Approvals

cULus Recognized

Phoenix Contact 2014 © - all rights reserved
http://www.phoenixcontact.com