


MATERIAL:
 Body:Nylon66, UL rated:94V-2 min
 Actuator:Nylon66, UL rated:94V-2 min
 Terminal:Brass,silver plated
 Rating: 40A 125V AC
 25A 250V AC
 Function:ON-OFF
 Protection Grade:IP65
 Contact Resistance: 50mΩ Max
 Insulation Resistance:100MΩ Min at DC 500V
 Dielectric Strength: 2000VAC 1 minute
 Dielectrical life: 10,000 cycles
 Mechanical life :50,000 cycles
 Operating Temperature: -20℃~80℃
 Safety Approval:



	X	Y
0.75~1.25	30.0+0.1	22.0+0.1
1.25~2.00	30.2+0.1	22.0+0.1
2.00~3.00	30.4+0.1	22.0+0.1



公差 TOLERANCES		.X±0.5	.XX±0.3	角度 ANGLE ±1°		单位 DIMENSION UNIT		mm.	
版本 VERSION	A0	比例尺 SCALE		1:1	日期 DATE	2020.11.23	品名 TITLE	图号 DRAWING NO	R-6-210-W5N-BB_0
核准 APPROVED BY		核对 CHECKED BY		绘图 DRAWN BY	孙成		R-6-210-W5N-BB		
版本 VER	变更说明 CHANGE DESCRIPTION	日期 DATE	ECN NO.						