


Features

- Metal silicon rectifier,majority carrier conduction
- Guard ring for transient protection
- Low power loss,high efficiency
- High surge capability
- High current capability,low VF
- For use in low voltage,high frequency inverters,free wheeling,and polarity protection applications
- Plastic material-UL flammability 94V-0

Mechanical Data

- Case: Molded plastic DO-201AD
- Polarity: Color band dented cathode end
- Mounting Position: Any



Maximum Ratings and Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified

Single phase,half wave,60Hz,resistive or inductive load

For capacitive load derate current by 20%

Type Number	SYMBOL	SR 1020	SR 1030	SR 1040	SR 1045	SR 1050	SR 1060	SR 1080	SR 10100	SR 10150	SR 10200	Unit
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	20	30	40	45	50	60	80	100	150	200	V
Maximum RMS Voltage	V _{RMS}	14	21	28	31.5	35	42	56	70	105	140	V
Maximum DC Blocking Voltage	V _{DC}	20	30	40	45	50	60	80	100	150	200	V
Maximum Average Forward Rectified Current.375"(9.5mm) lead length@T _L =100°C	IF(AV)	10.0										A
Peak Forward Surge Current 8.3ms Single half sine-wave superimposed on rated load (JEDEC Method)	IFSM	150										A
I ² t Rating for Fusing (t < 8.3ms)	I ² t	93.375										A ² s
Forward Voltage @IF=10.0A(Note 1)	V _{FM}	0.55				0.7		0.85		0.92		V
Peak Reverse Current @T _A =25°C	I _R	0.3						0.05				mA
At Rated DC Blocking Voltage @T _A =100°C		10						5				
Typical Junction Capacitance (Note2)	C _J	450										pF
Typical Thermal Resistance Junction to case	R _{θJA}	3.0										°C/W
Operating Temperature Range	T _J	-55 to +150										°C
/Storage Temperature Range	T _{STG}	-55 to +150										°C

Note:1. 300us Pulse Width,2%Duty Cycle

2. Measured at 1.0 MHz and Applied reverse Voltage of 4.0V D.C

FIG.1-FORWARD CURRENT DERATING CURVE




FIG.2-TYPICAL FORWARD CHARACTERISTICS




FIG.3-MAXIMUM NON-REPETITIVE SURGE





FIG.4-TYPICAL REVERSE CHARACTERISTICS



Important Notice and Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from DIYI.
- DIYI reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.
- DIYI disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- DIYI does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the here in document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications.

DIYI makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

- The products shown here in are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify DIYI for any damages resulting from such improper use or sale.
- Since DIYI uses lot number as the tracking base, please provide the lot number for tracking when complaining.