



**Material:**

1. CABLE: NON-UL 28AWG(7/0.127)TC\*14C INS:PVC+DRAIN WIRE(26AWG 7/0.16)+AL-FOIL/MYLAR  
PVC JACKET COLOR:BEIGE, OD:6.0±0.2mm
2. CONNECTOR:  
P1&P2:HD15P MALE GOLD FLASH CONTACT,  
NICKEL PLATED SHELL(THE 9TH PIN UNLOAD)
3. HOOD:MOLDED TYPE PVC 45P COLOR:BEIGE.
4. ELECTRICAL TEST:  
<1>100% OPEN SHORT & MIS WIRE TEST.  
<2>CONTACT RESISTANCE 3 Ohms MAX.  
<3>INSULATION RESISTANCE 20M Ohms MIN.
5. PACKING:SEE P-0039 REV.C PACKING DRAWING+EAN CODE  
PACKING TYPE: DB VP4  
(HANKING SIZE MUST BE SMALLER THAN PACKING)

| PIN Assignment |             |       |
|----------------|-------------|-------|
| P1             |             | P2    |
| 1              | WHITE       | 1     |
| 2              | GREY        | 2     |
| 3              | YELLOW      | 3     |
| 4              | PINK        | 4     |
| 5              | ORANGE      | 5     |
| 6              | RED         | 6     |
| 7              | BROWN       | 7     |
| 8              | GREEN       | 8     |
| 10             | BLUE        | 10    |
| 11             | PURPLE      | 11    |
| 12             | LIGHT GREEN | 12    |
| 13             | LIGHT BLUE  | 13    |
| 14             | BLACK       | 14    |
| 15             | WHITE/BLACK | 15    |
| Shell          | DRAIN       | Shell |

Ⓜ = Assmann logo



|          |   |
|----------|---|
| ITEM NO. | <b>AK376-3-R</b>  |
| TITLE    | VGA Monitor Connection cable -<br>HD D-Sub 15-pin Male <=> Male, 3 Meters |

**ASSMANN**  
Electronics, Inc.

1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283  
Toll Free: 1-877-277-6266 • Email: info@usa-assmann.com

THIS DRAWING IS UNPUBLISHED  
©Copyright 2010 by Assmann Electronic Components  
All International Rights Reserved