



MATERIALS:

Body: Brass, Tarnish Resistant Plating, Center Contact: Gold Plated Brass
Marking: "Pomona 3296"

RATINGS:

Operating Voltage: Shield/Earth: 30VAC/60VDC Max.
Inner conductor/Shield: 500VRMS Max.
Operating Temperature: +50°C. (+122°F.) Max.

ORDERING INFORMATION: Model 3296

All dimensions are in inches. Tolerances (except noted): .xx = $\pm .02$ " (.51 mm), .xxx = $\pm .005$ " (.127 mm).
All specifications are to the latest revisions. Specifications are subject to change without notice.
Registered trademarks are the property of their respective companies.

Made in USA

Pomona[®]

Model 3296 Adapter, Miniature Binding Posts To BNC Male

All dimensions are in inches. Tolerances (except noted): .xx = $\pm .02$ " (.51 mm), .xxx = $\pm .005$ " (.127 mm).
All specifications are to the latest revisions. Specifications are subject to change without notice.
Registered trademarks are the property of their respective companies.

Made in USA

6/9/99

SY/EH/LS

S:\Engineering\Release\DataSheets\FIukeDataSheet\3296_1_01.doc

Sales: 800-490-2361 Fax: 888-403-3360

Technical Assistance: 800-241-2060

PomonaACCESS 90761 (800) 444-6785 or (425) 446-6010

More drawings available at www.pomonaelectronics.com

Page 2 of 2