



Ø16.00
[.630 in]



PANEL CUTOUT
MAX. PANEL THICKNESS
10.0mm [.315 in]



▲ LAMP INDICATOR
CONTACT CONFIGURATION

Ø18.00
[.71 in]

Ø9.20
[.36 in]

▲ RING ILLUMINATION
RED / GREEN

Ø11.90
[.47 in]

▲ FLAT ACTUATOR
STAINLESS STEEL



▲ BODY
STAINLESS STEEL

1.50
[.06 in]
15.5
[.61 in]
16.5±1.0
[.65±.04 in]

▲ 20.0±1.0
[.79±.04 in]

(-)

M16x1.0

(-) (+)

8.40
[.33 in]

NOTE:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X = ±0.4
X.XX = ±0.25
3. OPERATING TEMP.: -20°C to 55°C
4. ▲ DENOTES CRITICAL PARAMETER.
- ▲ 5. ILLUMINATION COLOR: RED (FORWARD), GREEN (REVERSE)
- ▲ 6. ILLUMINATION BASE RATING: 1.8V (FORWARD), 2.8V (REVERSE)
- ▲ 7. HARDWARE SUPPLIED: O-RING AND HEXNUT (NOT SHOWN)
8. 2002/95/EC (ROHS) COMPLIANT



TITLE PV6F2PXSS-3G1

A	21992	RELEASE FOR PRODUCTION	9/21/15	MW
REV	PCR NO	DESCRIPTION	DATE	BY

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY
TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

SCALE 2:1	DATE 9/21/2015	DR MW	DWG 52-PV6F2PXSS3G1	REV A
--------------	-------------------	----------	------------------------	----------