




**Table 1. Device summary**

| Symbol      | Value  |
|-------------|--------|
| $I_{F(AV)}$ | 2 A    |
| $V_{RRM}$   | 100 V  |
| $T_j$ (max) | 175 °C |
| $V_F$ (max) | 0.65 V |

### Features

- Negligible switching losses
- High junction temperature capability
- Low leakage current
- Good trade-off between leakage current and forward voltage drop
- Avalanche capability specified

### Description

Schottky rectifiers designed for high frequency miniature switched mode power supplies such as adapters and on board DC/DC converters. Available in SMA, low-profile SMA, SMB, low-profile SMB.

# 1 Characteristics

**Table 2. Absolute ratings (limiting values -T<sub>amb</sub> = 25° C unless otherwise stated)**

| Symbol             | Parameter                                             |           |                                              | Value        | Unit |
|--------------------|-------------------------------------------------------|-----------|----------------------------------------------|--------------|------|
| V <sub>RRM</sub>   | Repetitive peak reverse voltage                       |           |                                              | 100          | V    |
| I <sub>F(AV)</sub> | Average forward current                               | SMA / SMB | T <sub>L</sub> = 130 °C δ = 0.5              | 2            | A    |
|                    |                                                       | SMAflat   | T <sub>L</sub> = 145 °C δ = 0.5              |              |      |
|                    |                                                       | SMBflat   | T <sub>L</sub> = 150 °C δ = 0.5              |              |      |
| I <sub>FSM</sub>   | Surge non repetitive forward current                  |           | t <sub>p</sub> = 10 ms sinusoidal            | 75           | A    |
| P <sub>ARM</sub>   | Repetitive peak avalanche power                       |           | t <sub>p</sub> = 1 μs T <sub>j</sub> = 25 °C | 2400         | W    |
| T <sub>stg</sub>   | Storage temperature range                             |           |                                              | -65 to + 175 | °C   |
| T <sub>j</sub>     | Maximum operating junction temperature <sup>(1)</sup> |           |                                              | 175          | °C   |

1.  $\frac{dP_{tot}}{dT_j} < \frac{1}{R_{th(j-a)}}$  condition to avoid thermal runaway for a diode on its own heatsink

**Table 3. Thermal resistance**

| Symbol               | Parameter        |         | Value | Unit |
|----------------------|------------------|---------|-------|------|
| R <sub>th(j-l)</sub> | Junction to lead | SMA     | 30    | °C/W |
|                      |                  | SMAflat | 20    |      |
|                      |                  | SMB     | 25    |      |
|                      |                  | SMBflat | 15    |      |

**Table 4. Static electrical characteristics**


| Symbol                        | Parameter               | Test conditions         |                                   | Min. | Typ. | Max. | Unit |
|-------------------------------|-------------------------|-------------------------|-----------------------------------|------|------|------|------|
| I <sub>R</sub> <sup>(1)</sup> | Reverse leakage current | T <sub>j</sub> = 25 °C  | V <sub>R</sub> = V <sub>RRM</sub> |      |      | 1    | μA   |
|                               |                         | T <sub>j</sub> = 125 °C |                                   |      | 0.4  | 1    | mA   |
| V <sub>F</sub> <sup>(2)</sup> | Forward voltage drop    | T <sub>j</sub> = 25 °C  | I <sub>F</sub> = 2 A              |      |      | 0.79 | V    |
|                               |                         | T <sub>j</sub> = 125 °C |                                   |      | 0.6  | 0.65 |      |
|                               |                         | T <sub>j</sub> = 25 °C  | I <sub>F</sub> = 4 A              |      |      | 0.88 |      |
|                               |                         | T <sub>j</sub> = 125 °C |                                   |      | 0.69 | 0.74 |      |

1. Pulse test: t<sub>p</sub> = 5 ms, δ < 2%  
 2. Pulse test: t<sub>p</sub> = 380 μs, δ < 2%


To evaluate the conduction losses use the following equation:

$$P = 0.56 \times I_{F(AV)} + 0.045 I_{F(RMS)}^2$$


**Figure 1. Average forward power dissipation versus average forward current**




**Figure 2. Average forward current versus ambient temperature ( $\delta = 0.5$ ) (SMA / SMB)**




**Figure 3. Average forward current versus ambient temperature ( $\delta = 0.5$ ) (SMBflat)**




**Figure 4. Average forward current versus ambient temperature ( $\delta = 0.5$ ) (SMAflat)**




**Figure 5. Normalized avalanche power derating versus pulse duration**




**Figure 6. Normalized avalanche power derating versus junction temperature**




**Figure 7. Relative variation of thermal impedance junction to ambient versus pulse duration (SMA)**




**Figure 8. Relative variation of thermal impedance junction to lead versus pulse duration (SMAflat)**




**Figure 9. Relative variation of thermal impedance junction to ambient versus pulse duration (SMB)**



**Figure 10. Relative variation of thermal impedance junction to lead versus pulse duration (SMBflat)**



**Figure 11. Reverse leakage current versus reverse voltage applied (typical values)**



**Figure 12. Junction capacitance versus reverse voltage applied (typical values)**




Figure 13. Forward voltage drop versus forward current (low level)




Figure 14. Forward voltage drop versus forward current (high level)




Figure 15. Thermal resistance junction to ambient versus copper surface under each lead (SMA)




Figure 16. Thermal resistance junction to ambient versus copper surface under each lead (SMAflat)




Figure 17. Thermal resistance junction to ambient versus copper surface under each lead (SMB)





Figure 18. Thermal resistance junction to ambient versus copper surface under each lead (SMBflat)




## 2 Package information

- Epoxy meets UL94, V0
- Lead-free packages

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: [www.st.com](http://www.st.com). ECOPACK® is an ST trademark.

**Figure 19. SMA dimension definitions**



**Table 5. SMA dimension values**

| Ref. | Dimensions  |      |        |       |
|------|-------------|------|--------|-------|
|      | Millimeters |      | Inches |       |
|      | Min.        | Max. | Min.   | Max.  |
| A1   | 1.90        | 2.45 | 0.075  | 0.094 |
| A2   | 0.05        | 0.20 | 0.002  | 0.008 |
| b    | 1.25        | 1.65 | 0.049  | 0.065 |
| c    | 0.15        | 0.40 | 0.006  | 0.016 |
| D    | 2.25        | 2.90 | 0.089  | 0.114 |
| E    | 4.80        | 5.35 | 0.189  | 0.211 |
| E1   | 3.95        | 4.60 | 0.156  | 0.181 |
| L    | 0.75        | 1.50 | 0.030  | 0.059 |

Figure 20. SMA footprint (dimensions in mm)




Figure 21. SMB dimension definitions




Table 6. SMB dimension values

| Ref. | Dimensions  |      |        |       |
|------|-------------|------|--------|-------|
|      | Millimeters |      | Inches |       |
|      | Min.        | Max. | Min.   | Max.  |
| A1   | 1.90        | 2.45 | 0.075  | 0.096 |
| A2   | 0.05        | 0.20 | 0.002  | 0.008 |
| b    | 1.95        | 2.20 | 0.077  | 0.087 |
| c    | 0.15        | 0.40 | 0.006  | 0.016 |
| E    | 5.10        | 5.60 | 0.201  | 0.220 |
| E1   | 4.05        | 4.60 | 0.159  | 0.181 |
| D    | 3.30        | 3.95 | 0.130  | 0.156 |
| L    | 0.75        | 1.50 | 0.030  | 0.059 |

Figure 22. SMB footprint (dimensions in mm)




Figure 23. SMAflat dimension definitions




Table 7. SMAflat dimensions

| Ref. | Dimensions  |      |      |        |       |       |
|------|-------------|------|------|--------|-------|-------|
|      | Millimeters |      |      | Inches |       |       |
|      | Min.        | Typ. | Max. | Min.   | Typ.  | Max.  |
| A    | 0.90        |      | 1.10 | 0.035  |       | 0.043 |
| b    | 1.25        |      | 1.65 | 0.049  |       | 0.065 |
| c    | 0.15        |      | 0.40 | 0.006  |       | 0.016 |
| D    | 2.25        |      | 2.95 | 0.088  |       | 0.116 |
| E    | 4.80        |      | 5.60 | 0.189  |       | 0.220 |
| E1   | 3.95        |      | 4.60 | 0.156  |       | 0.181 |
| L    | 0.75        |      | 1.50 | 0.030  |       | 0.059 |
| L1   |             | 0.50 |      |        | 0.019 |       |
| L2   |             | 0.50 |      |        | 0.019 |       |

Figure 24. SMAflat footprint dimensions




Figure 25. SMBflat dimension definitions





Table 8. SMBflat dimensions

| Ref.             | Dimensions  |      |      |        |       |       |
|------------------|-------------|------|------|--------|-------|-------|
|                  | Millimeters |      |      | Inches |       |       |
|                  | Min.        | Typ. | Max. | Min.   | Typ.  | Max.  |
| A                | 0.90        |      | 1.10 | 0.035  |       | 0.043 |
| b <sup>(1)</sup> | 1.95        |      | 2.20 | 0.077  |       | 0.087 |
| c <sup>(1)</sup> | 0.15        |      | 0.40 | 0.006  |       | 0.016 |
| D                | 3.30        |      | 3.95 | 0.130  |       | 0.156 |
| E                | 5.10        |      | 5.60 | 0.200  |       | 0.220 |
| E1               | 4.05        |      | 4.60 | 0.189  |       | 0.181 |
| L                | 0.75        |      | 1.50 | 0.029  |       | 0.059 |
| L1               |             | 0.40 |      |        | 0.016 |       |
| L2               |             | 0.60 |      |        | 0.024 |       |

1. Applies to plated leads

Figure 26. SMBflat footprint (dimensions in mm)



### 3 Ordering information

**Table 9. Ordering information**

| Order code  | Marking | Package | Weight  | Base qty | Delivery mode |
|-------------|---------|---------|---------|----------|---------------|
| STPS2H100A  | S21     | SMA     | 0.068 g | 5000     | Tape and reel |
| STPS2H100AF | F21     | SMAflat | 0.035 g | 10000    | Tape and reel |
| STPS2H100U  | G21     | SMB     | 0.107 g | 2500     | Tape and reel |
| STPS2H100UF | FG21    | SMBflat | 0.050 g | 5000     | Tape and reel |

### 4 Revision history

**Table 10. Document revision history**

| Date        | Revision | Changes                                                                                                      |
|-------------|----------|--------------------------------------------------------------------------------------------------------------|
| Jul-2003    | 4A       | Last update.                                                                                                 |
| Aug-2004    | 5        | SMA package dimensions update. Reference A1 max. changed from 2.70 (0.106 inches) to 2.03 mm (0.080 inches). |
| 08-Feb-2007 | 6        | Reformatted to current standards. Added ECOPACK statement. Added SMBflat package.                            |
| 15-Feb-2010 | 7        | Updated weight for SMBflat in <a href="#">Table 9</a> .                                                      |
| 24-Jun-2013 | 8        | Added SMAflat package                                                                                        |

**Please Read Carefully:**

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

**UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.**

**ST PRODUCTS ARE NOT AUTHORIZED FOR USE IN WEAPONS. NOR ARE ST PRODUCTS DESIGNED OR AUTHORIZED FOR USE IN: (A) SAFETY CRITICAL APPLICATIONS SUCH AS LIFE SUPPORTING, ACTIVE IMPLANTED DEVICES OR SYSTEMS WITH PRODUCT FUNCTIONAL SAFETY REQUIREMENTS; (B) AERONAUTIC APPLICATIONS; (C) AUTOMOTIVE APPLICATIONS OR ENVIRONMENTS, AND/OR (D) AEROSPACE APPLICATIONS OR ENVIRONMENTS. WHERE ST PRODUCTS ARE NOT DESIGNED FOR SUCH USE, THE PURCHASER SHALL USE PRODUCTS AT PURCHASER'S SOLE RISK, EVEN IF ST HAS BEEN INFORMED IN WRITING OF SUCH USAGE, UNLESS A PRODUCT IS EXPRESSLY DESIGNATED BY ST AS BEING INTENDED FOR "AUTOMOTIVE, AUTOMOTIVE SAFETY OR MEDICAL" INDUSTRY DOMAINS ACCORDING TO ST PRODUCT DESIGN SPECIFICATIONS. PRODUCTS FORMALLY ESCC, QML OR JAN QUALIFIED ARE DEEMED SUITABLE FOR USE IN AEROSPACE BY THE CORRESPONDING GOVERNMENTAL AGENCY.**

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2013 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Philippines - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

[www.st.com](http://www.st.com)