

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0440680280](#)
Status: **Active**
Description: 4.20mm (.165") Pitch Mini-Fit BMI™ Surface Mount Compatible Header, Dual Row, Vertical, 10 Circuits, 6.35mm (.250") PCB Thickness, with Snap-In Metal Pins, PA Polyamide Nylon 4/6, UL 94V-0, with Gold (Au) Over Nickel (Ni) Plating

Documents:	
3D Model	Product Specification PS-43810-001 (PDF)
Drawing (PDF)	RoHS Certificate of Compliance (PDF)

Agency Certification

CSA	LR19980
UL	E29179

General

Product Family	PCB Headers
Series	44068
Application	Board-to-Board, Wire-to-Board
Comments	Current = 13A max. per circuit when header is mated to a receptacle loaded with 45750 Mini-Fit Plus HCS™ Crimp Terminal Crimped to to 16 AWG wire. . See Molex product specification PS-45750-001 for additional current de-rating information.
Product Name	Mini-Fit BMI™

Physical

Breakaway	No
Circuits (Loaded)	10
Circuits (maximum)	10
Color - Resin	Black
Durability (mating cycles max)	30
First Mate / Last Break	No
Flammability	94V-0
Glow-Wire Compliant	No
Guide to Mating Part	Yes
Keying to Mating Part	None
Lock to Mating Part	Yes
Material - Metal	Brass
Material - Plating Mating	Gold
Material - Plating Termination	Gold
Material - Resin	High Temperature Thermoplastic
Number of Rows	2
Orientation	Vertical
PC Tail Length (in)	0.335 In
PC Tail Length (mm)	8.50 mm
PCB Locator	Yes
PCB Retention	Yes
PCB Thickness Recommended (in)	0.250 In
PCB Thickness Recommended (mm)	6.30 mm
Packaging Type	Tray
Pitch - Mating Interface (in)	0.165 In
Pitch - Mating Interface (mm)	4.20 mm
Plating min: Mating (µin)	30
Plating min: Mating (µm)	0.76
Plating min: Termination (µin)	30
Plating min: Termination (µm)	0.76




image - Reference only

EU RoHS
ELV and RoHS
Compliant
REACH SVHC
Not Reviewed
Halogen-Free
Status
Not Reviewed

China RoHS

Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.





Search Parts in this Series
[44068Series](#)

Mates With
[15-06-0101](#) Mini-Fit BMI™ Panel Mount Receptacle, [39-01-2105](#) Mini-Fit Jr.™ Receptacle, [15-24-7103](#) Mini-Fit BMI™ Receptacle Header

Polarized to Mating Part	Yes
Polarized to PCB	Yes
Shrouded	Fully
Stackable	No
Surface Mount Compatible (SMC)	Yes
Temperature Range - Operating	-40°C to +105°C
Termination Interface: Style	Through Hole
Electrical	
Current - Maximum per Contact	13A
Voltage - Maximum	600V
Solder Process Data	
Lead-free Process Capability	SMC & Wave Capable (TH only)
Process Temperature max. C	235
Material Info	
Reference - Drawing Numbers	
Packaging Specification	PK-43879-002
Product Specification	PS-43810-001
Sales Drawing	SD-44068-061
Test Summary	TS-43810-001

This document was generated on 05/14/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION



PCB LAYOUT: COMPONENT SIDE
RECOMMENDED PCB THICKNESS: SEE CHART

NOTES:

1) MATERIALS:

HOUSING: PA46 FILLED BLACK, UL94V-0

TERMINAL: BRASS

BOARD RETENTION CLIP: BRASS

2) FINISHES:

1 = 0.00254/(.000100) MIN TIN OVER NICKEL

2 = 0.00076/(.000030) MIN GOLD OVER NICKEL

3) PRODUCT SPECIFICATIONS: PS-43810-001

4) PACKAGING SPECIFICATION: PK-43879-002

5) PART MATES WITH MOLEX RECEPTACLE #5557 AND #42474, AND #42385 HEADER.

6) PART ALLOWS FOR 1.27/.050 MAX. MIS-ALIGNMENT WITH MATING HOUSINGS IN ANY DIRECTION.

7) CONNECTOR ASSEMBLIES ARE NOT TO BE MATED AND UNMATED WHILE CIRCUITS ARE LIVE.

8) THIS DIMENSION DOES NOT APPLY TO PARTS WITHOUT P.C. BOARD RETENTION CLIPS.

9) THIS PART CONFORMS TO CLASS B REQUIREMENTS OF COSMETIC SPECIFICATION PS-45499-002.

CKTS	DIM. "A"	DIM. "B"	DIM. "C"
4	18.81 .740	4.20 .165	16.60 .653
6	23.01 .906	8.40 .331	20.80 .819
8	27.21 1.071	12.60 .496	25.00 .984
10	31.41 1.237	16.80 .661	29.20 1.150
12	35.61 1.402	21.00 .828	33.40 1.315
14	39.81 1.567	25.20 .992	37.60 1.480
16	44.01 1.733	29.40 1.157	41.80 1.646
18	48.21 1.898	33.60 1.323	46.00 1.811
20	52.41 2.063	37.80 1.488	50.20 1.976
22	56.61 2.229	42.00 1.654	54.40 2.142
24	60.81 2.394	46.20 1.819	58.60 2.307

2	C1
1	C2
SHEET	REV

CORRECTED NOTE #2 EC NO: UCP2009-4772 DRAWN: TBENES CHKD: 2009/01/23 APPR: FSMITH 2009/01/26	DESCRIPTION	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM/IN		SCALE 1:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION
				mm	INCH	DRAWN BY JIWANG	DATE 2000/07/27	TITLE MINI-FIT JR BMI SMC VERTICAL HEADER ASM FOR 6.35/.250 THK PCB	
			4 PLACES	± ---	± ---	CHECKED BY BANDURA	DATE 2000/07/27		
			3 PLACES	± ---	± .010	APPROVED BY EDGLEY	DATE 2000/07/27	MOLEX INCORPORATED	
			2 PLACES	± 0.25	± .014	MATERIAL NO. SEE SHEET 2	DOCUMENT NO. SD-44068-061		SHEET NO. 1 OF 2
			1 PLACE	± 0.35	± ---	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS			
			ANGULAR ±1/2°		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				

	13	12	11	10	9	8	7	6	5	4	3	2	1																																																																			
J	<table><tr><td>FINISH:</td><td>I (SEE NOTE 2)</td><td>FINISH:</td><td>I (SEE NOTE 2)</td></tr><tr><td>DIM. D:</td><td>WITHOUT CLIP</td><td>DIM. D:</td><td>$\frac{(6.60 \pm 0.25)}{.260 \pm .010}$</td></tr><tr><td>PCB THICKNESS:</td><td>$\frac{(6.35 \pm 0.18)}{.250 \pm .007}$</td><td>PCB THICKNESS:</td><td>$\frac{(6.35 \pm 0.18)}{.250 \pm .007}$</td></tr><tr><td></td><td></td><td></td><td></td></tr><tr><td>CIRCUITS</td><td>MATERIAL NO.</td><td>CIRCUITS</td><td>MATERIAL NO.</td></tr><tr><td>04</td><td>44068-0244</td><td>04</td><td>44068-0266</td></tr><tr><td>06</td><td>44068-0245</td><td>06</td><td>44068-0267</td></tr><tr><td>08</td><td>X 44068-0246</td><td>08</td><td>X 44068-0268</td></tr><tr><td>10</td><td>44068-0247</td><td>10</td><td>44068-0269</td></tr><tr><td>12</td><td>X 44068-0248</td><td>12</td><td>X 44068-0270</td></tr><tr><td>14</td><td>44068-0249</td><td>14</td><td>44068-0271</td></tr><tr><td>16</td><td>X 44068-0250</td><td>16</td><td>X 44068-0272</td></tr><tr><td>18</td><td>44068-0251</td><td>18</td><td>44068-0273</td></tr><tr><td>20</td><td>X 44068-0252</td><td>20</td><td>X 44068-0274</td></tr><tr><td>22</td><td>X 44068-0253</td><td>22</td><td>X 44068-0275</td></tr><tr><td>24</td><td>44068-0254</td><td>24</td><td>44068-0276</td></tr></table>													FINISH:	I (SEE NOTE 2)	FINISH:	I (SEE NOTE 2)	DIM. D:	WITHOUT CLIP	DIM. D:	$\frac{(6.60 \pm 0.25)}{.260 \pm .010}$	PCB THICKNESS:	$\frac{(6.35 \pm 0.18)}{.250 \pm .007}$	PCB THICKNESS:	$\frac{(6.35 \pm 0.18)}{.250 \pm .007}$					CIRCUITS	MATERIAL NO.	CIRCUITS	MATERIAL NO.	04	44068-0244	04	44068-0266	06	44068-0245	06	44068-0267	08	X 44068-0246	08	X 44068-0268	10	44068-0247	10	44068-0269	12	X 44068-0248	12	X 44068-0270	14	44068-0249	14	44068-0271	16	X 44068-0250	16	X 44068-0272	18	44068-0251	18	44068-0273	20	X 44068-0252	20	X 44068-0274	22	X 44068-0253	22	X 44068-0275	24	44068-0254	24	44068-0276	I	H	G
FINISH:														I (SEE NOTE 2)	FINISH:	I (SEE NOTE 2)																																																																
DIM. D:														WITHOUT CLIP	DIM. D:	$\frac{(6.60 \pm 0.25)}{.260 \pm .010}$																																																																
PCB THICKNESS:														$\frac{(6.35 \pm 0.18)}{.250 \pm .007}$	PCB THICKNESS:	$\frac{(6.35 \pm 0.18)}{.250 \pm .007}$																																																																
CIRCUITS														MATERIAL NO.	CIRCUITS	MATERIAL NO.																																																																
04														44068-0244	04	44068-0266																																																																
06														44068-0245	06	44068-0267																																																																
08														X 44068-0246	08	X 44068-0268																																																																
10														44068-0247	10	44068-0269																																																																
12	X 44068-0248	12	X 44068-0270																																																																													
14	44068-0249	14	44068-0271																																																																													
16	X 44068-0250	16	X 44068-0272																																																																													
18	44068-0251	18	44068-0273																																																																													
20	X 44068-0252	20	X 44068-0274																																																																													
22	X 44068-0253	22	X 44068-0275																																																																													
24	44068-0254	24	44068-0276																																																																													
F	<table><tr><td>FINISH:</td><td>2 (SEE NOTE 2)</td><td>FINISH:</td><td>2 (SEE NOTE 2)</td></tr><tr><td>DIM. D:</td><td>WITHOUT CLIP</td><td>DIM. D:</td><td>$\frac{(6.60 \pm 0.25)}{.260 \pm .010}$</td></tr><tr><td>PCB THICKNESS:</td><td>$\frac{(6.35 \pm 0.18)}{.250 \pm .007}$</td><td>PCB THICKNESS:</td><td>$\frac{(6.35 \pm 0.18)}{.250 \pm .007}$</td></tr><tr><td></td><td></td><td></td><td></td></tr><tr><td>CIRCUITS</td><td>MATERIAL NO.</td><td>CIRCUITS</td><td>MATERIAL NO.</td></tr><tr><td>04</td><td>44068-0255</td><td>04</td><td>44068-0277</td></tr><tr><td>06</td><td>44068-0256</td><td>06</td><td>44068-0278</td></tr><tr><td>08</td><td>X 44068-0257</td><td>08</td><td>X 44068-0279</td></tr><tr><td>10</td><td>44068-0258</td><td>10</td><td>44068-0280</td></tr><tr><td>12</td><td>X 44068-0259</td><td>12</td><td>X 44068-0281</td></tr><tr><td>14</td><td>44068-0260</td><td>14</td><td>44068-0282</td></tr><tr><td>16</td><td>X 44068-0261</td><td>16</td><td>X 44068-0283</td></tr><tr><td>18</td><td>44068-0262</td><td>18</td><td>44068-0284</td></tr><tr><td>20</td><td>X 44068-0263</td><td>20</td><td>X 44068-0285</td></tr><tr><td>22</td><td>X 44068-0264</td><td>22</td><td>X 44068-0286</td></tr><tr><td>24</td><td>44068-0265</td><td>24</td><td>44068-0287</td></tr></table>													FINISH:	2 (SEE NOTE 2)	FINISH:	2 (SEE NOTE 2)	DIM. D:	WITHOUT CLIP	DIM. D:	$\frac{(6.60 \pm 0.25)}{.260 \pm .010}$	PCB THICKNESS:	$\frac{(6.35 \pm 0.18)}{.250 \pm .007}$	PCB THICKNESS:	$\frac{(6.35 \pm 0.18)}{.250 \pm .007}$					CIRCUITS	MATERIAL NO.	CIRCUITS	MATERIAL NO.	04	44068-0255	04	44068-0277	06	44068-0256	06	44068-0278	08	X 44068-0257	08	X 44068-0279	10	44068-0258	10	44068-0280	12	X 44068-0259	12	X 44068-0281	14	44068-0260	14	44068-0282	16	X 44068-0261	16	X 44068-0283	18	44068-0262	18	44068-0284	20	X 44068-0263	20	X 44068-0285	22	X 44068-0264	22	X 44068-0286	24	44068-0265	24	44068-0287	E	D	C
FINISH:														2 (SEE NOTE 2)	FINISH:	2 (SEE NOTE 2)																																																																
DIM. D:														WITHOUT CLIP	DIM. D:	$\frac{(6.60 \pm 0.25)}{.260 \pm .010}$																																																																
PCB THICKNESS:														$\frac{(6.35 \pm 0.18)}{.250 \pm .007}$	PCB THICKNESS:	$\frac{(6.35 \pm 0.18)}{.250 \pm .007}$																																																																
CIRCUITS														MATERIAL NO.	CIRCUITS	MATERIAL NO.																																																																
04														44068-0255	04	44068-0277																																																																
06														44068-0256	06	44068-0278																																																																
08														X 44068-0257	08	X 44068-0279																																																																
10														44068-0258	10	44068-0280																																																																
12	X 44068-0259	12	X 44068-0281																																																																													
14	44068-0260	14	44068-0282																																																																													
16	X 44068-0261	16	X 44068-0283																																																																													
18	44068-0262	18	44068-0284																																																																													
20	X 44068-0263	20	X 44068-0285																																																																													
22	X 44068-0264	22	X 44068-0286																																																																													
24	44068-0265	24	44068-0287																																																																													
B	X PRECEDING PART NUMBER DESIGNATES CIRCUIT SIZE IS NOT TOOLED PLEASE CONTACT FACTORY													A																																																																		
A																																																																																

SEE SHEET 1 EC NO: UCP2009-1250 DRWN: JKLOSTEMEIER 2008/11/24 CHKD: JBELL 2008/11/24 APPR: FSMITH 2008/11/24	REV	DESCRIPTION	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM/IN		SCALE 1:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION				
				4 PLACES	mm	INCH	DRAWN BY JIWANG	DATE 2000/07/27	TITLE MINI-FIT JR BMI SMC VERTICAL HEADER ASM FOR 6.35/.250 THK PCB					
					3 PLACES	± ---	± .010	CHECKED BY BANDURA			DATE 2000/07/27			
					2 PLACES	± 0.25	± .014	APPROVED BY EDGLEY			DATE 2000/07/27			
					1 PLACE	± 0.35	± ---							
				ANGULAR ±1/2°				MATERIAL NO.			DOCUMENT NO.		SHEET NO. 2 OF 2	
				DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				SEE CHART			SD-44068-061			
				SIZE				THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION						

1b_frame_C_P_ME_T Rev. D 2004/04/02	12	11	10	9	8	7	6	5	4	3	2	1
--	----	----	----	---	---	---	---	---	---	---	---	---