

Han-Modular ECO hood IP20 (with PE mark)



•	
Part number	09 14 001 0423
Specification	Han-Modular ECO hood IP20 (with PE mark)
HARTING eCatalogue	https://b2b.harting.com/09140010423

Image is for illustration purposes only. Please refer to product description.

ELV status

Identification				
Category	Hoods/Housings			
Series of hoods/housings	Han-Modular [®] ECO			
Type of hood/housing	Hood			
Description of hood/housing	With PE identification (pin 1 = PE)			
Version				
Locking type	Snap-in latches			
Size	Modular ECO			
Version	Top entry			
Cable entry	1x			
Technical characteristics				
Limiting temperature	-40 +85 °C			
Mating cycles	≥500			
Degree of protection acc. to IEC 60529	IP20			
Cable diameter	3 14.5 mm			
Material properties				
Material (hood/housing)	Polycarbonate (PC)			
Colour (hood/housing)	RAL 7032 (pebble grey)			
Material flammability class acc. to UL 94	V-0			
RoHS	compliant			

Page 1 / 2 | Creation date 2020-03-26 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric GmbH & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com

compliant



Material properties

China RoHS	e
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No

Specifications and approvals

Specifications	EN 60664-1 IEC 61984		
CE	Yes		
Commercial data			
Packaging size	2		
Net weight	33.34 g		

Net weight	33.34 g
Country of origin	Germany
European customs tariff number	85389099
eCl@ss	27440202 Shell for industrial connectors