


<b>Sales Region</b>	Worldwide (except Japan)
<b>Series</b>	GENESYS+
<b>Model</b>	G+Rack 60kW
<b>Status</b>	 Production
<b>Option Lineup</b>	<a href="#">Please refer to here.</a>
<b>Recommended EMC Filter</b>	
<b>Accessories</b>	<a href="#">Please refer to here.</a>



### Electrical Characteristics

Input	3-phase
Input Voltage Range[AC]	170 to 265Vac
Input Frequency Range	47 to 63Hz
Rated Output Voltage[DC]	300Vdc
Output Voltage[DC]	0 to 300Vdc
Rated Output Current	200A
Output Current	0 to 200A
Rated Output Power	60kW
Efficiency	90% Typ.
Voltage Ripple Noise	
Current Ripple Noise	

### Package Type & Size

Package Type	Rack DC System
Width(W)	553mm Nom. (21.77in Nom.)
Height(H)	1028mm Nom. (40.47in Nom.)
Depth(D)	902mm Nom. (35.51in Nom.)
Weight	200kg Typ. (440.9lbs Typ.)

### Other

Interfaces Included	LAN (LXI compliant)
	USB
	RS-232
	RS-485
Interface Options	Isolated analog voltage control
	GPIB
	EtherCAT
Operating Temp. Range	Modbus-TCP
	0 to 50°C

! Images are for reference only and show exemplary products.  
! This PDF document was created based on the data listed on the TDK Corporation website.  
! All specifications are subject to change without notice.

Safety Standard(Certified)	IEC61010-1 EN61010-1
Safety Standard(Conformed)	
Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.