
High Performance BGA Cooling Solutions w/ Thermal Tape Attachment





ATS Part#:

ATS-54230R-C1-R0

Description:

High Performance Extrusion, T412, BLACK-ANODIZED

Heat Sink Type: Straight Fin Heat Sink Attachment: Equivalent Part Number: ATS-54230R-C2-R0

THERMAL TAPE

*Image above is for illustration purpose only.

Features & Benefits

- · High aspect ratio, straight fin heat sinks that are ideal for compact PCB environments
- Designed specifically for BGAs and other surface mount packages .
- . Comes pre-assembled with high performance thermal interface material

Thermal Performance

		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	7.28 °C/W	5.94 °C/W	5.18 °C/W	4.66 °C/W	4.28 °C/W	3.99 °C/W	3.75 °C/W
	Ducted Flow	4.94	n/a	n/a	n/a	n/a	n/a	n/a

Product Detail

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	ТІМ	Finish
	23.0 mm	23.0 mm	19.5 mm	mm	T412	BLACK-ANODIZED
Image above is for illustration purpose only.	 Dimension ATS-5423 (Saint Go Thermal p applicatio ATS resent performant ATS certifier 	30R-C2-R0 is the ex bain C675). performance data ar n. rves the right to upd nce. ïes that this heat sir	height from the botto	nbly with an equivale ence only. Actual pe oducts without notic S-6 and REACH co	rformanc e to impr	al interface material e may vary by

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.



© 2012 Advanced Thermal Solutions, Inc. | 89-27 Access Road | Norwood MA | 02062 | USA