

IGBT Module-Chopper　　300A, 600V

PRHMB300E6
PRHMB300E6C

□ 回路図 : *CIRCUIT*



□ 外形寸法図 : *OUTLINE DRAWING*



Dimension: [mm]

□ 最大定格 : *MAXIMUM RATINGS* (T_C=25℃)

Item		Symbol	Rated Value				Unit
コレクタ・エミッタ間電圧 Collector-Emitter Voltage		V_{CES}	600				V
ゲート・エミッタ間電圧 Gate-Emitter Voltage		V_{GES}	±20				V
コレクタ電流 Collector Current	DC	I_C	300				A
	1ms	I_{CP}	600				
コレクタ損失 Collector Power Dissipation		P_C	1,040				W
接合温度 Junction Temperature Range		T_j	−40～+150				℃
保存温度 Storage Temperature Range		T_{stg}	−40～+125				℃
絶縁耐圧(Terminal to Base AC, 1minute) Isolation Voltage		V_{ISO}	2,500				$V_{(RMS)}$
締め付けトルク Mounting Torque	Module Base to Heatsink	F_{tor}	PDMB3006	3 (30.6)	PDMB300E6C	3 (30.6)	N・m (kgf・cm)
	Busbar to Main Terminal			3 (30.6)		2 (20.4)	

□ 電気的特性 : *ELECTRICAL CHARACTERISTICS* (T_C=25℃)

Characteristic		Symbol	Test Condition	Min.	Typ.	Max.	Unit
コレクタ遮断電流 Collector-Emitter Cut-Off Current		I_{CES}	V_{CE}= 600V, V_{GE}= 0V	−	−	1.0	mA
ゲート漏れ電流 Gate-Emitter Leakage Current		I_{GES}	V_{GE}= ±20V, V_{CE}= 0V	−	−	1.0	μA
コレクタ・エミッタ間飽和電圧 Collector-Emitter Saturation Voltage		$V_{CE(sat)}$	I_C= 300A, V_{GE}= 15V	−	2.1	2.6	V
ゲートしきい値電圧 Gate-Emitter Threshold Voltage		$V_{GE(th)}$	V_{CE}= 5V, I_C= 300mA	4.0	−	8.0	V
入力容量 Input Capacitance		C_{ies}	V_{CE}= 10V, V_{GE}= 0V, f= 1MHz	−	15,000	−	pF
スイッチング時間 Switching Time	上昇時間 Rise Time	t_r	V_{CC}= 300V R_L= 1.0Ω R_G= 3.6Ω V_{GE}= ±15V	−	0.15	0.40	μs
	ターンオン時間 Turn-on Time	t_{on}		−	0.30	0.75	
	下降時間 Fall Time	t_f		−	0.10	0.35	
	ターンオフ時間 Turn-off Time	t_{off}		−	0.40	0.80	

□フリーホイーリングダイオードの特性: *FREE WHEELING DIODE RATINGS & CHARACTERISTICS* (T_C=25℃)

Item		Symbol	Rated Value	Unit
順電流 Forward Current	DC	I_F	300	A
	1ms	I_{FM}	600	

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
順電圧 Peak Forward Voltage	V_F	I_F= 300A, V_{GE}= 0V	−	1.9	2.4	V
逆回復時間 Reverse Recovery Time	t_{rr}	I_F= 300A, V_{GE}= −10V di/dt= 600A/μs	−	0.15	0.25	μs

□ 熱的特性 : *THERMAL CHARACTERISTICS*

Characteristic		Symbol	Test Condition	Min.	Typ.	Max.	Unit
熱抵抗 Thermal Impedance	IGBT	Rth(j-c)	Junction to Case (Tc測定点チップ直下)	−	−	0.12	℃/W
	Diode			−	−	0.24	

日本インター株式会社

PRHMB300E6
PRHMB300E6C

Fig.1- Output Characteristics (Typical)




Fig.2- Output Characteristics (Typical)




Fig.3- Collector to Emitter On Voltage vs. Gate to Emitter Voltage (Typical)




Fig.4- Collector to Emitter On Voltage vs. Gate to Emitter Voltage (Typical)




Fig.5- Gate Charge vs. Collector to Emitter Voltage (Typical)




Fig.6- Capacitance vs. Collector to Emitter Voltage (Typical)




Fig.7- Collector Current vs. Switching Time (Typical)




Fig.8- Series Gate Impedance vs. Switching Time (Typical)




Fig.9- Collector Current vs. Switching Time




Fig.10- Series Gate Impedance vs. Switching Time




Fig.11- Collector Current vs. Switching Loss




Fig.12- Series Gate Impedance vs. Switching Loss




Fig.13- Forward Characteristics of Free Wheeling Diode (Typical)




Fig.14- Reverse Recovery Characteristics (Typical)




Fig.15- Reverse Bias Safe Operating Area




Fig.16- Transient Thermal Impedance

