

Product data sheet

Specifications



Delta 3 robot, P4, 3-4 axis, 15 kg permissible load, 0-1200 mm working envelop

VRKP4L0RNO00000

Product availability : Stock - Normally stocked in distribution facility

Price* : 42,700.00 USD

Main

Range of Product	Lexium P, T
Product or Component Type	Delta 3 robot
Device short name	P4
Design	Standard

Complementary

Number of axis	3...4
Operating position	Rotational 360°
Work envelope	0.00...47.24 in (0...1200 mm) diameter 0.00...16.73 in (0...425 mm) vertical
Repeat accuracy	0.1 mm
Permanent permissible load	33.07 lb(US) (15 kg)
Maximum actuation speed	32.81 ft/s (10 m/s)
Maximum acceleration	328.08 ft/s² (100 m/s²) at 1 kg 246.06 ft/s² (75 m/s²) at 1.5 kg
Net Weight	264.55 lb(US) (120 kg)
Range Compatibility	Lexium 62 ILM motor

Environment

Environmental characteristic	Normal environment High pressure cleaner Dust pollution resistance
------------------------------	--

Ordering and shipping details

Category	18357-PACDRIVE ROBOTIC
Discount Schedule	PC52
GTIN	3606485307138
Nbr. of units in pkg.	1
Package weight(Lbs)	286.60 lb(US) (130.0 kg)
Returnability	No

* Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	53.15 in (135 cm)
Package 1 width	47.24 in (120 cm)
Package 1 Length	39.37 in (100 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
PVC free	Yes