



Recommended P. C. B
Layout(±0.05)

Technical Date
 Pin(outer sleeve):Brass,machined CuZn38pb2
 Clip (Contact 4 Finger):Beryllium copper,heat treated
 Insulator:PBT UL94V-0 colour:black
 Gold Plated:2um"/80u"Ni,GF
 Current rating:3Amps
 Mechanical Life:min 500 cycles
 Contact resistance: 10mΩ max
 Dielectric strength:1000V
 Operating temperature:-40 °C to +105°C
 Soldering temperature:+255°C

X5621 F V -2xXX- C762 D1150 -1150
 ① ② ③ ④ ⑤ ⑥ ⑦

- 1.Series No
- 2.Category:F-Female
- 3.Welding Board Angle:V-Straight 180°
- 4.Row No-Pin No:2xXX-2x01Pin-2xXXPin
- 5.line spacing:C=7.62mm
- 6.Pin Length:D=11.50mm
- 7.1150:Type1150

| | | | |
|-----------------------------|----------|---------------|--------------------|
| X5621FV-2xXX-C762D1150-1150 | PBT | Brass | X5621W |
| PART NO | Material | Material(Pin) | Suitable XKB Wafer |

广东星坤科技股份有限公司

| | |
|------|-------------|
| ΔX | 日期 |
| ΔX | 日期 |
| ΔX | 日期 |
| MARK | DESCRIPTION |

文件工程章

| REVISIONS | DATE | REVISED | APPROVED | UNSPECIFIED TOLERANCES |
|-----------|------|---------|----------|------------------------|
| | | | | |
| | | | | |
| | | | | |
| | | | | |

| | | |
|--------------------------------------|-------------|-------------------------------------------|
| DSND | SCALE: N/A | MODEL TYPE: 2.54mm BTB Style Connector |
| DWN | VIEW: | PART NO.: X5621FV-2xXX-C762D1150-1150 |
| CHKD | UNIT: mm/in | DWG NO.: |
| APPD | SIZE: A4 | X-X5621FV-2xXX-C762D1150-1150 |
| XKB INDUSTRIAL PRECISION CO.,LIMITED | | WEIGHT SHEET REVISION 1/1 A0 |

