

MS-10-18



| | |
|-------------------------------|---|
| Sales Region | Worldwide |
| Series | MS |
| Status | Production |
| Feature | |
| Option | |
| Option Lineup | |
| Recommended EMC Filter | Please refer to here. |
| Accessories | Please refer to the catalog |



| Electrical Characteristics | |
|----------------------------|---------------|
| Input Voltage Range[AC] | 85 to 132V |
| Input Voltage Range[DC] | 90 to 165V |
| Efficiency | 80% Typ. |
| Rated Output Voltage[DC] | 18V |
| Output Voltage Range[DC] | 16.2 to 19.8V |
| Maximum Output Current | 3.5A |
| Maximum Output Power | 63W |

| Cases Shape & Size | |
|--------------------|------------|
| Case'□ shape | Unit |
| Width(W) | 43mm Nom. |
| Height(H) | 97mm Nom. |
| Depth(D) | 200mm Nom. |
| Weight | 690g Typ. |

| Other | |
|----------------------------|--------------------|
| Operating Temp. Range | -10 to 71°C |
| Cooling | Convection cooling |
| Safety Standard(Certified) | |
| Safety Standard(Conformed) | |

Remarks This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.