WEJ®


RoHS

BR2505W-2510W

SINGLE-PHASE BRIDGE RECTIFIER

FEATURES

- Low cost
- This series is UL recognized under component index, file number E127707
- High forward surge current capability
- Integrally molded heatsink provide very low thermal resistance.
- High isolation voltage from case to leads.
- High temperature soldering guaranteed: 260℃/10 second, at 5 lbs. (2.3kg) tension.



BR-15W/25W/35W

MECHANICAL DATA

- Case: Molded plastic body, suffic "N" for thinner type
- Terminal: Plated lead 0.040" (1.02mm) diameter
- Polarity: Polarity symbols marked on case.
- Mounting: Thru hole for #10 screw, 20 in,- lbs. Torqute Max.
- Weight: 0.61 ounce, 17.4gram(BR25W)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25℃ ambient temperature unless otherwise specified
Single phase, half wave, 60Hz, resistive or inductive load.
For capacitive load derate current by 20%

		SYMBOLS	BR2505W	BR251W	BR252W	BR254W	BR256W	BR258W	BR2510W	
Maximum Repetitive Peak Reverse Voltage		V_{RRM}	50	100	200	400	600	800	1000	Volts
Maximum RMS Voltage		V_{RMS}	35	70	140	280	420	560	700	Volts
Maximum DC Blocking Voltage		V_{DC}	50	100	200	400	600	800	1000	Volts
Maximum Average Forward Rectified Output Current, at T_C = 50℃ (Note 1, 2)		$I_{(AV)}$	25							Amps
Peak Forward Surge Current 8.3ms single half sine - wave superimposed on rated load (JEDEC method)		I_{FSM}	300							Amps
Rating for Fusing (t<8.3ms)		I^2t	373							A^2s
Maximum Instantaneous Forward Voltage Drop per bridge element at 12.5A		V_F	1.1							Volts
Maximum DC Reverse Current at rated DC blocking voltage per element	T_A = 25℃	I_R	10							μA
	T_A = 100℃		1.0							mA
Isolation Voltage from case to leads.		V_{ISO}	2500							V_{AC}
Typical Thermal Resistance (Note 1,2)		$R_{\theta JC}$	2.0							℃/W
Operating Temperature Range		T_J	(-65 to +150)							℃
Storage Temperature Range		T_{STG}	(-65 to +150)							

1. Unit mounted on 5" X 6" X 4.9" (12.8cm X 15.2cm X 12.4cm)Al. finned Plate.
2. Bolt down on heat-sink with silicon thermal compound between bridge and mounting sutfae for maximum heat transfer efficiency with # 10 screw.

WEJ ELECTRONIC CO.,LTD

FIG.1-DERATING CURVE FOR
OUTPUT RECTIFIED CURRENT




FIG.2-MAXIMUM NON-REPETITIVE PEAK
FORWARD SURGE CURRENT PER ELEMENT




FIG.3-TYPICAL FORWARD CHARACTERISTICS
PER BRIDGE ELEMENT




FIG.4-TYPICAL REVERSE CHARACTERISTICS
PER BRIDGE ELEMENT




FIG.5-TYPICAL JUNCTION CAPACITANCE
PER BRIDGE ELEMENT





FIG.6-MAXIMUM POWER DISSIPATION



WEJ ELECTRONIC CO.,LTD