

1		2			3	
DASH NO. RANGE	"D" DIA. RANGE	"E" DIMENSION	"G" GAP	"R" RADIUS	"T" GAUGE	
					"C"	"P"
-3 THRU -8	3/16" TO 1/2"	"D"/2 + .404	.07	.06	.031	.020
-9 THRU -17	9/16" TO 1-1/16"	"D"/2 + .471		.11	.050	.031
-18 THRU -32	1-1/8" TO 2"	"D"/2 + .500	.10	.13	.062	.040
-33 THRU -48	2-1/16" TO 3"		.13			.050

MATERIAL & FINISH CODES:

METAL: "C" 321 STAINLESS STEEL PER AMS 5510
FINISH: PASSIVATE PER AMS 2700, METHOD 1, CL. 1, TY. 6
"P" 17-7 PH STAINLESS STEEL PER AMS 5528
HEAT TREAT & STRESS RELIEVE TO TH1100 CONDITION
PER AMS 2759, AMS-H-6875, AFTER FORMING.
FINISH: PASSIVATE PER AMS 2700, METHOD 1, CL. 1, TY. 6


CUSHION: FIBERGLASS REINFORCED SILICONE PER AMS 3352, PWA 36450
COLOR: BROWN

EXAMPLE OF PART CALLOUT:


1" DIA. CLAMP, 17-7 PH STAINLESS STEEL W/WEDGED CUSHION

S634 W P 16


DIA "D" IN 1/16" INCREMENTS
METAL CODE
WEDGE CODE (OMIT IF NOT APPLICABLE)
BASIC PART NUMBER



5634



SECTION A-A
SCALE 1.5 : 1



SHEET 1 OF 1

REFERENCES: BACC10HM												
LIMITS ON DIMENSIONS UNLESS OTHERWISE SPECIFIED:	ANGULAR:	X	±	5°	 7100 LAMPSON AVE. P.O. BOX 5158 GARDEN GROVE, CA. 92846					FSCM/CAGE CODE No. 18076		
	DECIMAL:	.XX	±	.03						KEL	RPD	KEL
GENERAL MACHINE FINISHES EXCEPT AS NOTED: INTERPRET GEOMETRIC TOLERANCING PER: ASME-Y14.5M	PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF UMPCO, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF UMPCO, INC IS PROHIBITED.									03/22/8807/08/9603/22/88		
										DRAWNCHECKEDENGR		
					SCALE: NONE							
REMOVE ALL BURRS AND BREAK SHARP EDGES .010 MAX	ACT. WGHT.	-			CLAMP, SUPPORT, LOOP-TYPE, HIGH TEMP (600°F, 315°C) CUSHIONED					B	S634	
	CALC. WGHT.	-										PART AND/OR ASSEMBLY DESCRIPTION

NOTES:

- 1) INTEGRALLY MOLDED WEDGE IS FULL CONTOUR FROM -6 TO -24.
FOR SIZES -25 THRU -48, USE -24 WEDGE.
- 2) FOR BOEING PROCUREMENT, THE COMPLETE BOEING NUMBER AND "UMPCO" SHALL BE PERMANENTLY MARKED IN THIS AREA.
- 3) CLAMPS FURNISHED IN THE NORMAL OPEN (SPRINGBACK) CONDITION.
- 4) INSPECT PER MIL-C-8603 CLOSURE TEST.

1	2	3	4	5	6	7	8
---	---	---	---	---	---	---	---