
SL5225 THRU SL5262

SILICON PLANAR ZENER DIODES, 500 mW, MINIMELF PACKAGE

Silicon Planar Zener Diodes
Standard Zener voltage tolerance is ±20%. Add suffix "A" for ±10% tolerance and suffix "B" for ±5% tolerance. Other tolerance, non standard and higher Zener voltages upon requrst.


These diodes are also available in DO-35 case with the type designation 1N5225... 1N5262.

These diodes are delivered taped.
Details see "Taping".



Glass case MiniMELF

Weight approx. 0.05g
Dimensions in mm



Absolute Maximum Ratings (T_a = 25 °C)

	Symbol	Value	Unit
Zener Current see Table "Characteristics"			
Power Dissipation at T_{amb} = 75 °C	P_{tot}	500[1)]	mW
Junction Temperature	T_j	175	°C
Storage Temperature Range	T_S	-65 to + 175	°C

[1)] Valid provided that electrodes are kept at ambient temperature.

Characteristics at T_{amb} = 25 °C

	Symbol	Min.	Typ.	Max.	Unit
Thermal Resistance Junction to Ambient Air	R_{thA}	-	-	0.3[1)]	K/mW
Forward Voltage at I_F = 200 mA	V_F	-	-	1.1	V

[1)] Valid provided that electrodes are kept at ambient temperature.

SURGE COMPONENTS, INC. 1016 GRAND BLVD., DEER PARK, NY 11729
PHONE (631) 595-1818 FAX (631) 595-1283 www.surgecomponents.com

SL5225 THRU SL5262

Type	Nominal Zener voltage[3] at I_{ZT} V_Z V	Test current I_{ZT} mA	Maximum Zener Impedance [1] at I_{ZT} Z_{ZT} Ω	at I_{ZT} = 0.25 mA Z_{ZK} Ω	Typical temperature coefficient α_{VZ} %/K	Maximum reverse leakage current I_R µA	Test voltage Suffix A V_R V	Suffix B V_R V	Maximum regulator current[2] I_{ZM} mA
SL5225	3.0	20	29	1600	-0.075	50	0.95	1.0	152
SL5226	3.3	20	28	1600	-0.070	25	0.95	1.0	138
SL5227	3.6	20	24	1700	-0.065	15	0.95	1.0	126
SL5228	3.9	20	23	1900	-0.060	10	0.95	1.0	115
SL5229	4.3	20	22	2000	-0.055	5	0.95	1.0	106
SL5230	4.7	20	19	1900	±0.030	5	1.9	2.0	97
SL5231	5.1	20	17	1600	±0.030	5	1.9	2.0	89
SL5232	5.6	20	11	1600	+0.038	5	2.9	3.0	81
SL5233	6.0	20	7	1600	+0.038	5	3.3	3.5	76
SL5234	6.2	20	7	1000	+0.045	5	3.8	4.0	73
SL5235	6.8	20	5	750	+0.050	3	4.8	5.0	67
SL5236	7.5	20	6	500	+0.058	3	5.7	6.0	61
SL5237	8.2	20	8	500	+0.062	3	6.2	6.5	55
SL5238	8.7	20	8	600	+0.065	3	6.2	6.5	52
SL5239	9.1	20	10	600	+0.068	3	6.7	7.0	50
SL5240	10	20	17	600	+0.075	3	7.6	8.0	45
SL5241	11	20	22	600	+0.076	2	8.0	8.4	41
SL5242	12	20	30	600	+0.077	1	8.7	9.1	38
SL5243	13	9.5	13	600	+0.079	0.5	9.4	9.9	35
SL5244	14	9.0	15	600	+0.082	0.1	9.5	10	32
SL5245	15	8.5	16	600	+0.082	0.1	10.5	11	30
SL5246	16	7.8	17	600	+0.083	0.1	11.4	12	28
SL5247	17	7.4	19	600	+0.084	0.1	12.4	13	27
SL5248	18	7.0	21	600	+0.085	0.1	13.3	14	25
SL5249	19	6.6	23	600	+0.086	0.1	13.3	14	24
SL5250	20	6.2	25	600	+0.086	0.1	14.3	15	23
SL5251	22	5.6	29	600	+0.087	0.1	16.2	17	21
SL5252	24	5.2	33	600	+0.087	0.1	17.1	18	19.1
SL5253	25	5.0	35	600	+0.089	0.1	18.1	19	18.2
SL5254	27	4.6	41	600	+0.090	0.1	20	21	16.8
SL5255	28	4.4	44	600	+0.091	0.1	20	21	16.2
SL5256	30	4.2	49	600	-0.091	0.1	22	23	15.1
SL5257	33	3.8	58	700	+0.092	0.1	24	25	13.8
SL5258	36	3.4	70	700	+0.093	0.1	26	27	12.6
SL5259	39	3.2	80	800	+0.094	0.1	29	30	11.6
SL5260	43	3.0	93	900	+0.095	0.1	31	33	10.6
SL5261	47	2.7	105	1000	+0.095	0.1	34	36	9.7
SL5262	51	2.5	125	1100	+0.096	0.1	37	39	8.9

1) The Zener Impedance is derived from the 60 Hz AC voltage which results when an AC current having an RMS value equal to 10% of the Zener current (I_{ZT} or I_{ZK}) is superimposed on I_{ZT} or I_{ZK}. Zener Impedance is measured at two points to insure a sharp knee on the breakdown curve and to eliminate unstable units.

2) Valid provided that electrodes are kept at ambient temperature.

3) Measured under thermal equilibrium and DC test conditions.

SURGE COMPONENTS, INC. 1016 GRAND BLVD., DEER PARK, NY 11729
PHONE (631) 595-1818 FAX (631) 595-1283 www.surgecomponents.com