



**FEATURES**

- SMA connector
- Ideal for electron detection
- 100% internal QE
- Ultra high speed

Dimensions are in inch [metric] units.

**ELECTRO-OPTICAL CHARACTERISTICS AT 25°C**

PARAMETERS	TEST CONDITIONS	MIN	TYP	MAX	UNITS
Active Area	1mm x 1mm		1		mm <sup>2</sup>
Responsivity, $\mathcal{R}$	(see graphs on next page)				A/W
Reverse Breakdown Voltage, $V_R$	$I_R = 1\mu A$	55			Volts
Capacitance, C	$V_R = 0V$			40	pF
Rise Time	$R_L = 50\Omega, V_R = 52V$			700	psec
Dark Current	$V_R = 52V$	0		1	nA

**THERMAL PARAMETERS**

STORAGE AND OPERATING TEMPERATURE RANGE	
Ambient <sup>1</sup>	-10° TO 40°C <sup>1</sup>
Nitrogen or Vacuum	-20°C TO 80°C
Maximum Junction Temperature	70°C
Lead Soldering Temperature <sup>2</sup>	260°

<sup>1</sup>Temperatures exceeding these parameters may create oxide growth on the active area. Over time responsivity to low energy radiation and wavelengths below 150nm will be compromised.

<sup>2</sup>0.08" from case for 10 seconds.

Tighten to maximum torque of 5 inch/pounds.  
Permanent damage will result if higher torque values are used and warranty is voided.

