



MARK: KINGS 791-6-9 (DATE CODE)

791-6-9

REVISIONS

ISSUE	CHANGES
0	ER 34040 KH 08/20/92
B	REVISED PER DMF304 & ER35452 KPL 10/18/11

CUSTOMER SALES DRAWING

THIS DRAWING, THE DESIGNS AND IDEAS EMBODIED IN THE DEVICE TO WHICH IT RELATES, AND THE METHOD OF PRODUCING THE DEVICE, ARE THE PROPERTY OF WINCHESTER ELECTRONICS CORPORATION AND SHALL NOT BE EMPLOYED, COPIED, OR DISCLOSED TO ANYONE, IN ANY MANNER WITHOUT THE CONSENT OF WINCHESTER ELECTRONICS CORPORATION.

SCALE 4:1

APPROX SURFACE AREA

WAS: E-17486

CAGE CODE: 91836

REF: BOEING

JACK, PANEL, C

DRAWN KH DATE 06/01/92

DESIGN JT DATE 06/02/92

APPR. DATE



791-6-9

NOTES:

- FOR USE WITH BOEING BMS13-65 OH & ADAMS RUSSELL FC28Z CABLE.
- FOR CABLING INSTRUCTIONS SEE 3-546-2.
- FOR CRIMPING USE DIE KTH-2212
- INTERFACE PER MIL-STD-348, FIG. 302-2.
- FOR USE WITH .188 MAX. PANEL
- CENTER CONTACT (1-842-30MA9) SUPPLIED UNASSEMBLED.
- MARK PACKAGE: KINGS 791-6-9 (DATE CODE)
- MATERIALS:
INSULATOR-TEFLON, ASTM D1710
K-GRIP SLEEVE-COMMERCIAL BRONZE, ASTM B135
CENTER CONTACT-BER. COP., ASTM B196
ALL OTHER METAL PARTS-BRASS, ASTM B16
- FINISHES:
CENTER CONTACT: .000050 MIN GOLD PLATE, PER ASTM B488 OVER .000050 MIN. NICKEL PER AMS-QQ-N-290 (RoHS)
ALL OTHER METAL PARTS: .000050 MIN NICKEL PER AMS-QQ-N-290 OVER .000050 MIN COPPER PER ASTM B734 (RoHS)
- ELECTRIAL CHARACTERISTICS:
NOMINAL IMPEDANCE-50 OHMS
FREQUENCY RANGE-DC TO 11 GHZ
WORKING VOLTAGE-1000 VRMS
- WEIGHT: 26.5 GRAMS