

## STAF 14 STI-L




Image is for illustration purposes only. Please refer to product description.

Part number	09 70 014 2613
Specification	STAF 14 STI-L
HARTING eCatalogue	<a href="https://b2b.harting.com/09700142613">https://b2b.harting.com/09700142613</a>

### Identification

Category	Inserts
Series	Staf®

### Version

Termination method	Solder termination
Gender	Male
Size	10 A
Number of contacts	14

### Technical characteristics

Conductor cross-section	2.5 mm <sup>2</sup>
Rated current	10 A
Rated voltage	25 V
Rated voltage	25 V AC 60 V DC
Rated impulse voltage	0.8 kV
Pollution degree	3
Rated voltage acc. to UL	50 V
Rated voltage acc. to CSA	50 V
Insulation resistance	>10 <sup>10</sup> Ω
Contact resistance	≤2 mΩ
Limiting temperature	-40 ... +100 °C



Pushing Performance

## Technical characteristics

Mating cycles  $\geq 500$

## Material properties

Material (insert)	Polyamide (PA)
Colour (insert)	Black
Material (contacts)	Copper alloy
Surface (contacts)	Silver plated
Material flammability class acc. to UL 94	HB
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	Yes
REACH SVHC substances	Lead

## Specifications and approvals

Specifications	EN 60664-1 IEC 61984
UL / CSA	UL 1977 ECBT2.E235076

## Commercial data

Packaging size	1
Net weight	37.07 g
Country of origin	Romania
European customs tariff number	85366990
eCl@ss	27440205 Contact insert for industrial connectors