

# BA14E14M

by Burndy
Catalog ID: BA14E14M

Prop 65 Notice

TERMINAL-POLYVINYLCHLORIDE INSULATED, RING , 600 VOLTS MAX. 105° C MAX.

## Product Details

### General

| | |
|---|---|
| Connector Type | Terminal |
| Feature - Barrel Style | Shrouded |
| Insulation | Y |
| Insulation Type | Vinyl |
| Material | Copper |
| Physical Attribute - Number of Holes | 1 |
| Physical Attribute - Tongue Type | Ring |
| Plated | Y |
| Plating Type | Tin - Electro Plated |
| Trade Name | VINYLUG™ |
| Type | Ring Tongue |
| UPC | 781810028988 |
| UPC 12 Digit | 7818100289888 |

### Dimensions

| | |
|---|---|
| Dimension - Hole Size fraction | 10/37 |
| Dimension - Hole Size inch | 0.27 in |
| Dimension - Length Overall inch | 0.99 in |
| Dimension - Pad Width inch | 0.40 in |
| Dimension - Stud Size inch | 1/4 |
| Dimension - Z inch | 0.36 in |

### Conductor Related

| | |
|---|---|
| Conductor - Copper Solid Size | 16 AWG;15 AWG;14 AWG |
| Conductor - Copper Solid Size Range | 16 AWG-14 AWG |
| Conductor - Copper Str Size | 16 AWG;14 AWG |
| Conductor - Copper Str Size Range | 16 AWG-14 AWG |
| Conductor Type | CU C Str-Size |

### Certifications and Compliance

| | |
|---|---|
| Certification - CSA Approved | Yes |

| | |
|---|---|
| Certification - ETL | No |
| Certification - UL Recognized | No |
| Certification - cULus | No |
| Industry Standard(s) | UL467 |
| Standards - Industry Standards Met | UL467 |
| Standards - RoHS Compliance Status | CM |
| UL Listed | Yes |

## Logistics

| | |
|---|---|
| Minimum Pack Quantity | 2000 |

**For further technical assistance, please contact us**

**BURNDY Headquarters**
47 East Industrial Park Drive
Manchester, New Hampshire 03109

**Customer Service Hours:**
8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)