


Domiled

Synonymous with function and performance, the Domiled series is perfectly suited for a variety of cross-industrial applications due to its small package outline, durability and superior brightness.



Features:

- > High brightness surface mount LED using thin film technology.
- > 120° viewing angle.
- > Small package outline (LxWxH) of 3.2 x 2.8 x 1.8mm.
- > Qualified according to JEDEC moisture sensitivity Level 2.
- > Compatible to both IR reflow soldering.
- > Environmental friendly; RoHS compliance.
- > Qualified based on AEC-Q101 Standard.
- > Passed Corrosion Resistant Test.



Applications:

- > Automotive: Interior applications.
- > Infrared illumination.
- > Sensor technology.
- > IR data transmission.



Optical Characteristics at Tj=25°C

Part Ordering Number	Peak Wavelength	Viewing Angle°	Radiant Intensity @ IF = 70mA		Ie(mW/sr) <i>Appx. 1.3</i> Max.
			Min.	Typ.	
DR8-NJS-R-1	850nm	120	10.0	15.0	20.0

Electrical Characteristics at Tj=25°C

Part Number	Vf @ If = 70mA <i>Appx. 3.1</i>		Vr @ Ir = 10uA
	Typ. (V)	Max. (V)	Min. (V)
DR8-NJS	1.7	2.1	5

Absolute Maximum Ratings


	Maximum Value	Unit
DC forward current	70	mA
Peak pulse current; (tp ≤ 100µs, Duty cycle = 0.005)	700	mA
Reverse voltage	5	V
ESD threshold (HBM)	2000	V
LED junction temperature	110	°C
Operating temperature	-40 ... +100	°C
Storage temperature	-40 ... +100	°C
Power dissipation (at room temperature)	140	mW
Thermal resistance		
- Junction / ambient, Rth JA	420	K/W
- Junction / solder point, Rth JS	200	K/W
(Mounting on FR4 PCB, pad size ≥ 16 mm ² per pad)		

Luminous Intensity Group at Tj=25°C

Brightness Group	Luminous Intensity I _e (mW/sr)
R	10.0 - 20.0


Relative Radiant Intensity Vs Forward Current

$I_e/I_e(70\text{mA}) = f(I_F); T_j = 25^\circ\text{C}$




Forward Current Vs Forward Voltage

$I_F = f(V_F); T_j = 25^\circ\text{C}$




Maximum Current Vs Temperature

$I_F = f(T)$



Relative Spectral Emission

$I_{rel} = f(\lambda); T_j = 25^\circ\text{C}; I_F = 70\text{mA}$




Allowable Forward Current Vs Duty Ratio

$(T_j = 25^\circ\text{C}; t_p \leq 10\mu\text{s})$




Radiation Pattern




Relative Forward Voltage Vs Junction Temperature

$$\Delta V_F = V_F - V_F(25^\circ\text{C}) = f(T_j); I_F = 70\text{mA}$$




Relative Radiant Intensity Vs Junction Temperature

$$I_e/I_e(25^\circ\text{C}) = f(T_j); I_F = 70\text{mA}$$




Relative Wavelength Vs Junction Temperature

$$\Delta \lambda_{\text{dom}} = \lambda_{\text{dom}} - \lambda_{\text{dom}}(25^\circ\text{C}) = f(T_j); I_F = 70\text{mA}$$




DomiLED • IR : DR8-NJS Package Outlines



Material


Material	
Lead-frame	Cu Alloy With Ag Plating
Package	High Temperature Resistant Plastic, PPA
Encapsulant	Epoxy
Soldering Leads	Sn-Sn Plating

Recommended Solder Pad




Taping and orientation


- Reels come in quantity of 2000 units.
- Reel diameter is 180 mm.




Packaging Specification



Packaging Specification




	Average 1pc DomiLED/Multi DomiLED	1 completed bag (2000pcs)
Weight (gram)	0.034	240 ± 10



For DomiLED

Cardboard Box Size	Dimensions (mm)	Empty Box Weight (kg)	Reel / Box
Super Small	325 x 225 x 190	0.38	9 reels MAX
Small	325 x 225 x 280	0.54	15 reels MAX
Medium	570 x 440 x 230	1.46	60 reels MAX
Large	570 x 440 x 460	1.92	120 reels MAX

Recommended Pb-free Soldering Profile



Appendix

1) **Brightness:**

- 1.1 Luminous intensity is measured with an internal reproducibility of $\pm 8\%$ and an expanded uncertainty of $\pm 11\%$ (according to GUM with a coverage factor of $k=3$).
- 1.2 Luminous flux is measured with an internal reproducibility of $\pm 8\%$ and an expanded uncertainty of $\pm 11\%$ (according to GUM with a coverage factor of $k=3$).
- 1.3 Radiant intensity is measured with an internal reproducibility of $\pm 8\%$ and an expanded uncertainty of $\pm 11\%$ (according to GUM with a coverage factor of $k=3$).
- 1.4 Radiant flux is measured with an internal reproducibility of $\pm 8\%$ and an expanded uncertainty of $\pm 11\%$ (according to GUM with a coverage factor of $k=3$).

2) **Color:**

- 2.1 Chromaticity coordinate groups are measured with an internal reproducibility of ± 0.005 and an expanded uncertainty of ± 0.01 (accordingly to GUM with a coverage factor of $k=3$).
- 2.2 DOMINANT wavelength is measured with an internal reproducibility of $\pm 0.5\text{nm}$ and an expanded uncertainty of $\pm 1\text{nm}$ (accordingly to GUM with a coverage factor of $k=3$).

3) **Voltage:**

- 3.1 Forward Voltage, V_f is measured with an internal reproducibility of $\pm 0.05\text{V}$ and an expanded uncertainty of $\pm 0.1\text{V}$ (accordingly to GUM with a coverage factor of $k=3$).

Revision History

Page	Subjects	Date of Modification
-	Initial Release	27 Sep 2017
1	Typo Error on Features and Product Photo	17 Oct 2017

NOTE

All the information contained in this document is considered to be reliable at the time of publishing. However, DOMINANT Opto Technologies does not assume any liability arising out of the application or use of any product described herein.

DOMINANT Opto Technologies reserves the right to make changes to any products in order to improve reliability, function or design.

DOMINANT Opto Technologies products are not authorized for use as critical components in life support devices or systems without the express written approval from the Managing Director of DOMINANT Opto Technologies.

About Us

DOMINANT Opto Technologies is a dynamic company that is amongst the world's leading automotive LED manufacturers. With an extensive industry experience and relentless pursuit of innovation, DOMINANT's state-of-art manufacturing and development capabilities have become a trusted and reliable brand across the globe. More information about DOMINANT Opto Technologies, a ISO/TS 16949 and ISO 14001 certified company, can be found under <http://www.dominant-semi.com>.

Please contact us for more information:

DOMINANT Opto Technologies Sdn. Bhd.
Lot 6, Batu Berendam, FTZ Phase III, 75350 Melaka, Malaysia
Tel: (606) 283 3566 Fax: (606) 283 0566
E-mail: sales@dominant-semi.com