
New Jersey Semi-Conductor Products, Inc.

20 STERN AVE.
SPRINGFIELD, NEW JERSEY 07081
U.S.A.

TELEPHONE: (973) 376-2922
(212) 227-6005
FAX: (973) 376-8960

germanium signal diodes

Type	V_R max. (V)	I_O max. (mA)	I_O V_F=1V min. (mA)	I_R max. (μA)	V_R (V)	Case
gold bond						T_{amb} = 25°C
1N 34GB	75	50	5	30	10	 DO 7 glass (CB-26)
1N 55A	170	50	4	500	150	
1N 96	75	30	20	800	50	
1N 96A	75	70	40	500	50	
1N 98	100	60	20	100	50	
1N 98A	100	60	40	100	50	
1N 99	100	60	10	200	80	
1N 100A	100	70	40	50	50	
1N 117	75	30	10	100	50	
1N 118	75	60	20	100	50	
1N 118A	75	70	40	100	50	
1N 126A	75	30	5	850	50	
1N 270	100	90	200	100	50	
1N 276	100	60	40	20	10	
1N 277	125	75	100	250	50	
1N 281	75	75	100	500	50	
1N 283	25	100	200	20	10	
1N 949	50	100	10	100	50	

NJ Semi-Conductors reserves the right to change test conditions, parameter limits and package dimensions without notice. Information furnished by NJ Semi-Conductors is believed to be both accurate and reliable at the time of going to press. However NJ Semi-Conductors assumes no responsibility for any errors or omissions discovered in its use. NJ Semi-Conductors encourages customers to verify that datasheets are current before placing orders.