
PROTEK DEVICES
Only One Name Means ProTek'Tion™

LCD05C thru LCD24C

LOW CAPACITANCE TVS ARRAY

APPLICATIONS



16 PIN DIP

- ✔ Ethernet - 10/100 Base T
- ✔ RS-485
- ✔ xDSL & ATM
- ✔ SCSI & USB
- ✔ Audio/Video I/O Ports

IEC COMPATIBILITY (EN61000-4)

- ✔ 61000-4-2 (ESD): Air - 15kV, Contact - 8kV
- ✔ 61000-4-4 (EFT): 40A - 5/50ns
- ✔ 61000-4-5 (Surge): 24A, 8/20µs Level 2 (Line-Ground) & Level 3 (Line-Line)


FEATURES

- ✔ 800 Watts Peak Pulse Power per Line (tp=8/20µs)
- ✔ Bidirectional Configuration
- ✔ ESD Protection > 40 kilovolts
- ✔ Available in Five (5) Voltage Types: 5V to 24V
- ✔ Standard Dual-In-Line Package
- ✔ Protects Up to Eight (8) Lines
- ✔ ***LOW CAPACITANCE: 15pF***

MECHANICAL CHARACTERISTICS

- ✔ Molded 16 Pin Dual-In-Line (DIP) Package
- ✔ Weight 1.2 grams (Approximate)
- ✔ Flammability rating UL 94V-0
- ✔ Packaging: 25 Pieces Per Tube
- ✔ Marking: Logo, Part Number, Date Code & Pin One Defined By Dot on Top of Package

PIN CONFIGURATION



DEVICE CHARACTERISTICS

MAXIMUM RATINGS @ 25°C Unless Otherwise Specified			
PARAMETER	SYMBOL	VALUE	UNITS
Peak Pulse Power (t_p = 8/20µs) - See Figure 1	P_{PP}	800	Watts
Operating Temperature	T_J	-55°C to 150°C	°C
Storage Temperature	T_{STG}	-55°C to 150°C	°C

ELECTRICAL CHARACTERISTICS PER LINE @ 25°C Unless Otherwise Specified							
PART NUMBER (Notes 1)	RATED STAND-OFF VOLTAGE V_{WM} VOLTS	MINIMUM BREAKDOWN VOLTAGE @ 1mA $V_{(BR)}$ VOLTS	MAXIMUM CLAMPING VOLTAGE (See Fig. 2) @ I_P = 1 A V_C VOLTS	MAXIMUM CLAMPING VOLTAGE (See Fig. 2) @ 8/20µs V_C @ I_{PP}	MAXIMUM LEAKAGE CURRENT @V_{WM} I_D µA	MAXIMUM CAPACITANCE @ 0V, 1 MHz C pF	TEMPERATURE COEFFICIENT OF $V_{(BR)}$ $\theta V_{(BR)}$ mV/°C
LCD05C	5.0	6.0	9.8	24V @ 45A	100	15	3
LCD08C	8.0	8.5	12.3	25.5V @ 40A	10	15	9
LCD12C	12.0	13.3	19.0	32V @ 34A	4	15	16
LCD15C	15.0	16.7	25.5	38V @ 27A	4	15	17
LCD24C	24.0	26.7	40.0	48V @ 22A	4	15	26

Note 1: Tested on pin pairs 1 & 16, 2 & 15, 3 &14, 4 & 13, 5 & 12, 6 & 11, 7 & 10 and 8 & 9.

FIGURE 1
PEAK PULSE POWER VS PULSE TIME





FIGURE 2
PULSE WAVE FORM



GRAPHS

FIGURE 3
POWER DERATING CURVE






FIGURE 4
OVERSHOOT & CLAMPING VOLTAGE FOR LCD05C



ESD Test Pulse: 12 kilovolt, 1/30ns (waveform)

FIGURE 5
TYPICAL CLAMPING VOLTAGE VS PEAK PULSE CURRENT FOR LCD05C



APPLICATION NOTE

The LCA Series are low capacitance, bidirectional TVS arrays that are designed to protect I/O or high speed data lines from the damaging effects of ESD or EFT. This product series has a surge capability of 800 Watts P_{PP} per line for an 8/20µs waveshape and offers ESD protection > 40kV.


BIDIRECTIONAL COMMON-MODE CONFIGURATION (Figure 1)

Ideal for use in USB applications, the LCD Series provides up to eight (8) lines of protection in a common-mode configuration as depicted in Figure 1.

Circuit connectivity is as follows:

- ✔ Pins 2, 3, 4, 5, 6, and 7 are connected to ground.
- ✔ Pins 15 and 14 connected to Port #1 D- and D+.
- ✔ Pins 13 and 12 connected to Port #2 D+ and D-.
- ✔ Pins 11 and 10 connected to Port #3 D+ and D-.

Figure1. Typical Common- Mode USB Protection Circuit




CIRCUIT BOARD LAYOUT RECOMMENDATIONS

Circuit board layout is critical for Electromagnetic Compatibility (EMC) protection. The following guidelines are recommended:


- ✔ The protection device should be placed near the input terminals or connectors. By placing the TVS close to the connectors, the device will divert the transient current immediately before it can be coupled into the nearby traces.
- ✔ The path length between the TVS devices and the protected line should be minimized
- ✔ All conductive loops including power and ground loops should be minimized
- ✔ The transient current return path to ground should be kept as short as possible to reduce parasitic inductance.
- ✔ Ground planes should be used whenever possible. For Multilayer PCBs, use ground vias.

PACKAGE OUTLINE & DIMENSIONS

PACKAGE OUTLINE



16 PIN DIP



DIMENSIONS

DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	-	19.8	-	0.780
B	6.10	6.60	0.240	0.260
C	7.37	7.87	0.290	0.310
D	0.25	0.50	0.010	0.020
E	0°	10°	0°	10°
F	0.51	-	0.020	-
G	-	5.08	-	0.200
H	3.17	-	0.125	-
I	-	1.78	-	0.070
J	0.84 TYP	0.84 TYP	0.033 TYP	0.033 TYP
K	0.38	0.53	0.015	0.021
L	2.54 TYP	2.54 TYP	0.100 TYP	0.100 TYP

NOTES:

1. Dimensions are exclusive of mold flash and metal burrs.

BULK ORDERING NOMENCLATURE:

1. No Suffix = Product Shipped in Tubes of 25 pcs per Tube.

Outline & Dimensions: Rev 1 - 11/01, 06003

COPYRIGHT © ProTek Devices 2003
SPECIFICATIONS: ProTek reserves the right to change the electrical and or mechanical characteristics described herein without notice (except JEDEC).

DESIGN CHANGES: ProTek reserves the right to discontinue product lines without notice, and that the final judgement concerning selection and specifications is the buyer's and that in furnishing engineering and technical assistance, ProTek assumes no responsibility with respect to the selection or specifications of such products.

ProTek Devices
2929 South Fair Lane, Tempe, AZ 85282
Tel: 602-431-8101 Fax: 602-431-2288
E-Mail: sales@protekdevices.com
Web Site: www.protekdevices.com