



# PC PSU FSP400-60APN(85)

## DESCRIPTION

This specification describes a 400 watts power supply. With +5V stand-by, second 12V rail and remote ON/OFF control for ATX-12V system and a "Power factor collector (PFC)" circuit to meet EPA requirement of input range with in 230V/50Hz.

## APPLICATION

Desktop

## WATTAGE

**Wattage:** 400W

## DIMENSION

**Dimension:** 140mm(L) x 150mm(W) x 86mm(H)

## PRODUCT HIGHLIGHT

**Efficiency Level:** Bronze  
**Erp Lot:** <0.5W  
**Input Voltage:** 230V

## INPUT SPECIFICATION

**Input Range:** 200-240 Vac  
**Input Frequency:** 47-63 Hz  
**Input Current:** 3Amp (maximum) at 230 Vrms/ 50 Hz. .

## OUTPUT SPECIFICATION

**Output Rise Time:** +3.3V 20mS (maximum)  
+5V 20mS (maximum)  
+12 V1 20mS (maximum)  
+12 V2 20mS (maximum)  
-12 V 20mS (maximum)



## SAFETY STANDARD APPROVAL



## GENERAL SPECIFICATION

**Efficiency:** Bronze  
**PWOK Delay Time:** 500ms > PWOK > 100ms  
**EMC Performance:** EN55022 class B  
EN55024  
EN 61000-3-2  
EN 61000-3-3

## ENVIRONMENTAL SPECIFICATION

**TEMP.Range:** Storage Temperature: -40°C to +70°C

**MTBF:** The power supply reliability, when calculated by "Bellcore" latest revision are exceed 100,000 hours with all output at maximum load and an ambient temperature of 25°C.

The special requirement is for cooling fan that MTTF be guarantee over 30,000 hours at 25°C ambient temperature.

## \*Output Voltage and Current Rating

	+3.3V	+5V	+12V1	+12V2	-12V	+5Vsb
<b>Ripple-Noise(R-P) mV</b>	50mV	50mV	5mV	120mV	200mV	50mV
<b>Regulation Load %</b>	±5%	±5%	±5%	±5%	±10%	±5%
<b>Output Max.(A)</b>	24A	2.5A	17A	17A	0.3A	15A
<b>Output Min.(A)</b>	0.5A	0.3A	0.5A	0.5A	0A	0A

## NOTES

- +3.3V & +5V total output not exceed 120W.
- When +5V is load to 15A, the +3.3V maximum load is 13.6A.
- When +3.3V is load to 24A, the +5V maximum load is 8A.
- +12V1 & +12V2 total output not exceed 336W

This content is subject to change, please refer to specification for more detail.  
FSP reserve the right to change the content without prior notice