



□ 回路図 : CIRCUIT



□ 外形寸法図 : OUTLINE DRAWING



Dimension: [mm]

□ 最大定格 : MAXIMUM RATINGS ($T_c = 25^\circ\text{C}$)

Item	Symbol	Rated Value	Unit
コレクタ・エミッタ間電圧 Collector-Emitter Voltage	V_{CES}	1,200	V
ゲート・エミッタ間電圧 Gate-Emitter Voltage	V_{GES}	± 20	V
コレクタ電流 Collector Current	DC	400	A
	1ms	800	
コレクタ損失 Collector Power Dissipation	P_C	1,900	W
接合温度範囲 Junction Temperature Range	T_j	$-40 \sim +150$	$^\circ\text{C}$
保存温度範囲 Storage Temperature Range	T_{stg}	$-40 \sim +125$	$^\circ\text{C}$
絶縁耐圧 (Terminal to Base AC, 1 minute) Isolation Voltage	V_{ISO}	2,500	V (RMS)
締め付けトルク Mounting Torque	Module Base to Heatsink	3 (30.6)	N·m (kgf·cm)
	Busbar to Main Terminal		

□ 電気的特性 : ELECTRICAL CHARACTERISTICS ($T_c = 25^\circ\text{C}$)

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
コレクタ遮断電流 Collector-Emitter Cut-Off Current	I_{CES}	$V_{CE} = 1200\text{V}, V_{GE} = 0\text{V}$	—	—	8.0	mA
ゲート漏れ電流 Gate-Emitter Leakage Current	I_{GES}	$V_{GE} = \pm 20\text{V}, V_{CE} = 0\text{V}$	—	—	1.0	μA
コレクタ・エミッタ間飽和電圧 Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = 400\text{A}, V_{GE} = 15\text{V}$	—	1.9	2.4	V
ゲートしきい値電圧 Gate-Emitter Threshold Voltage	$V_{GE(th)}$	$V_{CE} = 5\text{V}, I_C = 400\text{mA}$	4	—	8	V
入力容量 Input Capacitance	C_{ies}	$V_{CE} = 10\text{V}, V_{GE} = 0\text{V}, f = 1\text{MHz}$	—	25,000	—	pF
スイッチング時間 Switching Time	上昇時間 Rise Time	$V_{CC} = 600\text{V}$ $R_g = 1\Omega$ $V_{GE} = \pm 15\text{V}$	—	0.25	0.45	μs
	ターンオン時間 Turn-on Time		—	0.40	0.70	
	下降時間 Fall Time		—	0.25	0.35	
	ターンオフ時間 Turn-off Time		—	0.80	1.10	

□ フリーホイーリングダイオードの特性 : FREE WHEELING DIODE RATINGS & CHARACTERISTICS ($T_c = 25^\circ\text{C}$)

I t e m		S y m b o l	R a t e d V a l u e			U n i t
順 電 流 Forward Current	DC	I _v	4 0 0			A
	1 m s	I _{FM}	8 0 0			

C h a r a c t e r i s t i c		S y m b o l	T e s t C o n d i t i o n	M i n .	T y p .	M a x .	U n i t
順 電 圧 Peak Forward Voltage		V _F	I _F = 400A, V _{GE} = 0V	—	1 . 9	2 . 4	V
逆 回 復 時 間 Reverse Recovery Time		t _{rr}	I _F = 400A, V _{GE} = -10V di/dt= 800A/μs	—	0 . 2	0 . 3	μ s

□ 熱的特性 : THERMAL CHARACTERISTICS

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
熱抵抗 Thermal Impedance	IGBT	Junction to Case	—	—	0.065	$^\circ\text{C}/\text{W}$
	Diode		—	—	0.12	

Fig.1- Output Characteristics (Typical)




Fig.2- Collector to Emitter On Voltage vs. Gate to Emitter Voltage (Typical)




Fig.3- Collector to Emitter On Voltage vs. Gate to Emitter Voltage (Typical)




Fig.4- Gate Charge vs. Collector to Emitter Voltage (Typical)




Fig.5- Capacitance vs. Collector to Emitter Voltage (Typical)




Fig.6- Collector Current vs. Switching Time (Typical)




Fig.7- Series Gate Impedance vs. Switching Time (Typical)




Fig.8- Forward Characteristics of Free Wheeling Diode (Typical)




Fig.9- Reverse Recovery Characteristics (Typical)




Fig.10- Reverse Bias Safe Operating Area




Fig.11- Transient Thermal Impedance

