



SAW Components

SAW RF filter

Automotive telematics

Series/type:	B4309
Ordering code:	B39202B4309P810
Date:	May 11, 2011
Version:	2.1



SAW Components

B4309

SAW RF filter

1950.00 MHz

Data Sheet




Application

- Low-loss RF filter for mobile telephone WCDMA systems, transmit path (Tx)
- Unbalanced to unbalanced operation
- Very low insertion attenuation
- Low amplitude ripple
- Very low Error Vector Magnitude (EVM)
- High Rx-suppression
- Usable passband 60 MHz




Features

- Package size 1.4 x 1.1 x 0.4 mm³
- Package code QCS5P
- RoHS compatible
- Approximate weight 0.003 g
- Package for **Surface Mount Technology (SMT)**
- Ni, gold-plated terminals
- AEC-Q200 qualified component family (operable temperature range -40°C to +85°C)
- **Electrostatic Sensitive Device (ESD)**
- Moisture Sensitivity Level 3



Pin configuration

- 1 Input
- 4 Output
- 2,3,5 to be grounded





SAW Components

B4309

SAW RF filter

1950.00 MHz

Data Sheet



Characteristics

Temperature range for specification: $T = -20\text{ °C to }+85\text{ °C}$
 Terminating source impedance: $Z_S = 50\ \Omega$
 Terminating load impedance: $Z_L = 50\ \Omega$

		min.	typ. @ 25 °C	max.	
Center frequency	f_C	—	1950.0	—	MHz
Maximum insertion attenuation	$\alpha_{\max}$	—	2.3	3.0	dB
1920.00 ... 1980.00 MHz					
Amplitude ripple (p-p)	$\Delta\alpha$	—	1.1	1.8	dB
1920.00 ... 1980.00 MHz					
VSWR		—	1.8	2.2	
1920.00 ... 1980.00 MHz					
Error Vector Magnitude	EVM ¹⁾	—	1.0	3.0	%
@fCarrier 1922.50 ... 1977.50 MHz					
Attenuation	α				
50.00 ... 960.00 MHz		27	34	—	dB
960.00 ... 1575.00 MHz		25	35	—	dB
1575.00 ... 1576.00 MHz		32	35	—	dB
1576.00 ... 1730.00 MHz		30	35	—	dB
1730.00 ... 1880.00 MHz		30	38	—	dB
2025.00 ... 2050.00 MHz		35	54	—	dB
2110.00 ... 2170.00 MHz		35	38	—	dB
2200.00 ... 3100.00 MHz		33	37	—	dB
3100.00 ... 3960.00 MHz		30	42	—	dB
3960.00 ... 6000.00 MHz		20	34	—	dB

¹⁾ Error Vector Magnitude (EVM) based on definition in 3GPP TS 25.141



SAW Components

B4309


SAW RF filter

1950.00 MHz


Data Sheet



Transfer function



Transfer function (wideband)



Please read *cautions and warnings* and *important notes* at the end of this document.



SAW Components

B4309

SAW RF filter


1950.00 MHz

Data Sheet




Smith chart


S11 function




normal impedance: 50.00 Ω



S22 function



normal impedance: 50.00 Ω



Please read *cautions and warnings* and *important notes* at the end of this document.

**SAW Components****B4309****SAW RF filter****1950.00 MHz**

Data Sheet

**Maximum ratings**

Operable temperature range	T	−40/+85	°C	cw signal
Storage temperature range	T _{stg}	−40/+85	°C	
DC voltage	V _{DC}	0	V	
Source power	P _S	10	dBm	



SAW Components	B4309
SAW RF filter	1950.00 MHz

Data Sheet



References

Type	B4309
Ordering code	B39202B4309P810
Marking and package	C61157-A8-A9
Packaging	F61074-V8212-Z000
Date codes	L_1126
S-parameters	B4309_NB.s2p B4309_WB.s2p See file header for port/pin assignment table.
Soldering profile	S_6001
RoHS compatible	defined as compatible with the following documents: "DIRECTIVE 2002/95/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 27 January 2003 on the restriction of the use of certain hazardous substances in electrical and electronic equipment. 2005/618/EC from April 18th, 2005, amending Directive 2002/95/EC of the European Parliament and of the Council for the purposes of establishing the maximum concentration values for certain hazardous substances in electrical and electronic equipment."
Moldability	Before using in overmolding environment, please contact your EPCOS sales office.
Matching coils	See Inductor pdf-catalog http://www.tdk.co.jp/tefe02/coil.htm#aname1 and Data Library for circuit simulation http://www.tdk.co.jp/etvcl/index.htm

For further information please contact your local EPCOS sales office or visit our webpage at www.epcos.com.

Published by EPCOS AG

Systems, Acoustics, Waves Business Group

P.O. Box 80 17 09, 81617 Munich, GERMANY

© EPCOS AG 2011. This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information or the type in question please also contact one of our Sales Offices.

Please read *cautions and warnings and important notes* at the end of this document.



Important notes

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health (e.g. in accident prevention or life-saving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of an electronic component.
3. **The warnings, cautions and product-specific notes must be observed.**
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as hazardous)**. Useful information on this will be found in our Material Data Sheets on the Internet (www.epcos.com/material). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order. We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available. The aforementioned does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.
6. Unless otherwise agreed in individual contracts, **all orders are subject to the current version of the "General Terms of Delivery for Products and Services in the Electrical Industry" published by the German Electrical and Electronics Industry Association (ZVEI)**.
7. The trade names EPCOS, BAOKE, Alu-X, CeraDiode, CSMP, CSSP, CTVS, DeltaCap, DigiSiMic, DSSP, FormFit, MiniBlue, MiniCell, MKD, MKK, MLSC, MotorCap, PCC, PhaseCap, PhaseCube, PhaseMod, PhiCap, SIFERRIT, SIFI, SIKOREL, SilverCap, SIMDAD, SiMic, SIMID, SineFormer, SIOV, SIP5D, SIP5K, ThermoFuse, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at www.epcos.com/trademarks.